



- 105° C
- Snap In
- Reusable

Nylon KO bushings are snapped into punched holes in panels to protect wires from the rough edges.

| CAT NO | UPC   | SIZE   | STD | MSTR | WT/STD | UNIT |
|--------|-------|--------|-----|------|--------|------|
| 1210D  | 12100 | 1/2"   | 100 | 1000 | 0.45#  | C    |
| 1211D  | 12110 | 3/4"   | 100 | 1000 | 0.66#  | C    |
| 1212D  | 12120 | 1"     | 100 | 1000 | 0.99#  | C    |
| 1213D  | 12130 | 1-1/4" | 50  | 500  | 0.70#  | C    |
| 1214D  | 12140 | 1-1/2" | 25  | 250  | 0.46#  | C    |
| 1215D  | 12150 | 2"     | 25  | 250  | 0.93#  | C    |
| 1216D  | 12160 | 2-1/2" | 25  | 250  | 1.20#  | C    |

## Anti-Short Bushings PC 5680



- Plastic
- Fits Armored Cable
- Prevents Shorts

Anti-Short bushings are used to protect wire insulation from the jagged or sharp cut edges of BX or flex. Priced per 100 pieces.

| CAT NO | UPC   | FLEX  | CABLE SIZE              | PKG | STD  | MSTR | WT/STD | UNIT |
|--------|-------|-------|-------------------------|-----|------|------|--------|------|
| 0      | 11600 | 5/16" | 14/2, 14/3, 12/2        | 100 | 1000 | 1000 | 0.75#  | C    |
| 1      | 11601 | 3/8"  | 14/4, 6/1, 4/1, 12/3    | 100 | 1000 | 1000 | 0.30#  | C    |
| 2      | 11602 | 7/16" | 12/4, 10/2, 10/3, 2/1   | 50  | 500  | 500  | 0.35#  | C    |
| 3      | 11603 | 1/2"  | 10/4, 8/2, 8/3, 1/1     | 50  | 500  | 500  | 0.40#  | C    |
| 4      | 11604 | 3/4"  | 8/4, 6/2, 6/3, 4/2, 4/3 | 50  | 500  | 500  | 0.40#  | C    |

## K.O. Seals PC 5440



- Snap In
- Steel
- Zinc Plated

Snap in K.O. seals are used to seal up holes punched in panels or knockouts from outlet boxes. They are held in place by spring tension. Available in sizes from 1/2" thru 2".

| CAT NO | UPC   | SIZE   | STD | MSTR | WT/STD | UNIT |
|--------|-------|--------|-----|------|--------|------|
| KO50   | 16000 | 1/2"   | 100 | 1000 | 1.44#  | C    |
| KO75   | 16010 | 3/4"   | 100 | 1000 | 1.62#  | C    |
| KO100  | 16020 | 1"     | 100 | 500  | 2.10#  | C    |
| KO125  | 16030 | 1-1/4" | 50  | 100  | 1.45#  | C    |
| KO150  | 16040 | 1-1/2" | 50  | 50   | 2.14#  | C    |
| KO200  | 16050 | 2"     | 25  | 25   | 1.44#  | C    |

## Three Piece K.O. Seals PC 5450



- Assembled\*
- Includes Screw and Threaded Strap
- Steel
- Zinc Plated

Three piece K.O. seals are used to seal up holes punched in panels or knockouts from outlet boxes. They are held in place by a screw inserted through the seal into a threaded strap on the opposite side of the opening. Available in sizes from 1/2" thru 6". Three piece K.O. seals are embossed to centralize in knockout. Installs from the inside or outside of any box without rearranging wires. One screw secures unit. Size is stamped into seal.

| CAT NO | UPC   | SIZE   | STD | MSTR | WT/STD | UNIT |
|--------|-------|--------|-----|------|--------|------|
| D10S*  | 10240 | 1/2"   | 100 | 100  | 2.62#  | C    |
| D20S*  | 10242 | 3/4"   | 50  | 50   | 1.73#  | C    |
| D30S*  | 10244 | 1"     | 25  | 25   | 1.33#  | C    |
| D40S   | 10246 | 1-1/4" | 25  | 25   | 1.74#  | C    |
| D50S   | 10248 | 1-1/2" | 10  | 10   | 1.03#  | C    |
| D60S   | 10250 | 2"     | 10  | 10   | 1.46#  | C    |
| D70S   | 10252 | 2-1/2" | 10  | 10   | 2.16#  | C    |
| D80S   | 10254 | 3"     | 10  | 10   | 3.11#  | C    |
| D90S   | 10256 | 3-1/2" | 10  | 10   | 3.97#  | C    |
| D100S  | 10258 | 4"     | 10  | 10   | 5.81#  | C    |
| D110S  | 10260 | 4-1/2" | 10  | 10   | 10.45# | C    |
| D120S  | 10262 | 5"     | 10  | 10   | 13.33# | C    |
| D130S  | 10264 | 6"     | 10  | 10   | 14.10# | C    |