



MP1095WS MULTI-PACK SOLUTION

Power, surge protection and USB charging solutions for home and office electronics

The Cyberpower MP1095WS combo pack comes with one eight-outlet surge protector strip with USB-A and USB-C and one six-outlet Wall-Tap surge protector with USB-A and USB-C.

The eight-outlet surge protector in this combo pack provides 2700 joules of protection to prevent damaging power spikes and surges from reaching your electronics. It features two USB ports (one 2.4A USB-A port and one 15W USB-C port) that will charge USB enabled mobile devices and small electronics. The P806UC36A has a six-foot power cord, a low-profile plug that fits in tight spaces, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.

The six-outlet surge protector wall-tap in this combo pack provides 2000 joules of protection to prevent damaging power spikes and surges from reaching your electronics. It features two USB ports (one 2.4A USB-A port and one 15W USB-C port) that will charge USB enabled mobile devices and small electronics. The P6WSUC has swiveling outlets that rotate 90 degrees to help with cord management, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.



TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES — P6WSUC | WALL-TAP

- Wall-Tap with USB
- AC outlets: 6
- Outlet type: NEMA 5-15R
- Surge suppression: 2000J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 15W
- Plug type: NEMA 5-15P
- Warranty: One-Year Limited

FEATURES — P806UC36A | POWER STRIP

- Power Strip with USB
- AC outlets: 8
- Outlet type: NEMA 5-15R
- Surge suppression: 2700J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 15W
- Plug type: NEMA 5-15P
- Plug style: Right-angle 45° offset
- Power cord length: 6 ft.
- Warranty: One-Year Limited

MP1095WS

MULTI-PACK SOLUTION

SPECIFICATIONS

	P806UC36A POWER STRIP	P6WSUC WALL-TAP
INPUT		
Voltage	125V	
Plug Type	NEMA 5-15P	
Plug Style	Right Angle, 45° Offset Right	Three Prong Direct Plug-in
Cord Length	6 ft	Wall-tap
OUTPUT		
Outlet Type	NEMA 5-15R	
Outlets - Total	8	6
Output Voltage	125V	
USB Charge Ports	1 USB-A, 1 USB-C	
USB-A Charge Port Output	5V / 2.4A	
USB-C Charge Port Output	5V / 15W	
SURGE PROTECTION & FILTERING		
Attenuation	32 dB	
Surge Suppression	2700J	2000J
Clamping Voltage	600 V (L-N, L-G, N-G)	
Response Time	< 1 Nanosecond	
EMI/RFI Filtration	150 KHz to 100 MHz	
INDICATORS		
LED Indicators	Protected (green) Grounded (green)	
PHYSICAL		
Color	White	
Keyhole Mounting Slots	No	

	P806UC36A POWER STRIP	P6WSUC WALL-TAP
DIMENSIONS		
Physical Dimensions - Width/Height/ Depth (cm)	9.91 x 3.1 x 19.81 cm	10.31 x 16.23 x 5.54 cm
Physical Dimensions - Width/Height/ Depth (mm)	99 x 31 x 198 mm	103 x 162 x 55 mm
Physical Dimensions - Width/Height/ Depth (in.)	3.9 x 1.22 x 7.8 in.	4.06 x 6.39 x 2.18 in.
SHIPPING DIMENSIONS		
Shipping Dimensions - Width/Height/ Depth (cm)	18 x 36.5 x 6 cm	
Shipping Dimensions - Width/Height/ Depth (mm)	180 x 365 x 60 mm	
Shipping Dimensions - Width/Height/ Depth (in)	7.09 x 14.37 x 2.36 in.	
Shipping Weight (kg)	1.09 kg	
Shipping Weight (lbs.)	2.40 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1363, 1449, 1310, cUL, FCC, DOE VI, CEC/ IC, NRCan	UL498A, 1449, 1310, cUL, FCC, DOE VI, CEC/ IC, NRCan
WARRANTY		
Product Warranty	One-Year Limited Warranty	
Connected Equipment Guarantee	Yes	
CEG Amount	\$100,000	