


Tremaine




Colors



White
VTL TRWH




Ivory
VTL TRIV



Pearl
VTL TRPE




Gray
VTL TRGR



Black
VTL TRBL

Sizes



24" x 48" x 8mm Rectified



24" x 24" x 8mm Rectified



12" x 24" x 8mm



8" x 24" x 8mm Rectified

TREMAINE

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" rectified	24.00" x 48.00"	10.00mm	Matte & Polished
24" x 24"	24.00" x 24.00"	8.00mm	Matte & Polished
12" x 24"	12.00" x 24.00"	8.00mm	Matte & Polished
8" x 24" rectified	8.00" x 24.00"	8.00mm	Polished
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
9" x 11" Hexagon Mosaic	9.00" x 11.00"	Matte & Polished
2" x 2" Mosaic	12.00" x 12.00"	Matte & Polished
3" x 12" Bullnose	3.00" x 12.00"	Matte & Polished
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

MATTE AND POLISHED	
Breaking Strength (ASTM C648 or ISO 10545-4)	≥400 lb/ft2
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤0.4%
Certifications	Greenguard Bureau Veritas NSF EPD
Country of Origin	USA
Shade Variation Code	v3



Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Glazed Porcelain



Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
SURFACES
COMMERCIAL