



PORTABLE AIR CONDITIONER

8,500 | 10,000 | 12,000 | 13,500 BTU



**3PORT8500A
3PORT10000A**



**3PORT12000
3PORT13500**

	3PORT8500A	3PORT10000A	3PORT12000	3PORT13500
UPC CODE	842149002480	842149002497	842149002503	842149002510
COOLING BTU (ashrae)	8,500	10,000	12,000	13,500
COOLING BTU (SACC)	6,000	7,100	8,000	10,000
DOE SACC COVERAGE (sq. ft.)	190	215	245	290
CEER	6.51	7.0	7.22	7.9
ENERGY STAR RATED	—	—	—	—
FAN SPEEDS (Cool/Fan)	2/2	2/2	3/3	3/3
AMPS	8.0	9.0	12	11.7
WATTS	870	1010	1255	1365
DECIBELS (Hi/Md/Lo)	53/-/51.5	53/-/51.5	51.6/50/48.9	54.0/52.5/51.5
VENT HOSE LENGTH (in.)	59	59	59	59
TIMER	✓	✓	✓	✓
UNIT DIMENSION (WxHxD) (in.)	11.75 × 27.75 × 11.5	11.75 × 27.75 × 11.5	17.5 × 28.75 Z × 13.75	17.5 × 28.75 × 13.75
PKG. DIMENSION (WxHxD) (in.)	13.75 × 35 × 13	13.75 × 35 × 13	19 × 35 × 15.25	19 × 35 × 15.75
CONTAINER QTY. (20' /40' /40' HQ)	238/478/714	238/478/714	146/294/448	146/294/448
WEIGHT (Net/Gross) (lbs.)	50/57.5	50/58	60.5/70	70/81.5
REFRIGERATION	R32	R32	R32	R32
OUTLET CONFIGURATION	 15A-115V	 15A-115V	 15A-115V	 15A-115V



FOLLOW ME
Portable remote control
thermostat feature for
total room coverage

SLIDER KIT & QUICK CONNECT VENT HOSE

Included with ALL
portable AC units



FEATURES

- Electronic controls
- Temperature output range of 62°F–86°F (17°C–30°C)
- Bucketless drain system
- Auto restart function
- Easy to install & operate
- Sleep mode
- Easy access washable filter
- Full function remote control
- Easy roll casters
- Variable cooling speeds
- CEC Compliant

