

DOUBLE-COATED POLYETHYLENE FILM — SYNTHETIC RUBBER



CONFORMABLE

AGGRESSIVE ADHESIVE

DESCRIPTION

A white non-oriented polyethylene film coated on both sides with a high grade synthetic rubber based pressure sensitive adhesive. Recommended for carpet installation and a wide range of industrial applications.

MAIN FEATURES

- Aggressive synthetic rubber-based adhesive.
- Very conformable.

APPLICATIONS

- Splicing.
- Holding.
- Joining and mounting applications.
- Carpet installation.

TECHNICAL DATA

Colour	White
Backing	Polyethylene film
Adhesive	Synthetic rubber based
Liner	Polysilicone type
Thickness without liner	3 mil
Adhesion	50 oz/in
Tensile strength	4 lb/in
Elongation	100%
Temperature Range	-18°C to 65°C (0°F to 150°F)
Application Temperature	16°C to 49°C (60°F to 120°F)

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.