



Main

| | |
|------------------------------|---|
| Range | TeSys TeSys Deca |
| Device short name | GVAD |
| Product or Component Type | Auxiliary contact block |
| Product Compatibility | GV2ME GV2L GV3P GV2P GV3L GV2LE GV2RT |
| Mounting Location | Left side |
| Auxiliary contacts operation | Fault signal 1 NC |
| Pole contact composition | 1 NO + 1 NC |

Complementary

| | |
|---|--|
| [Ui] rated insulation voltage | 690 V IEC 60947-1 300 V UL 508 300 V CSA C22.2 No 14 |
| [Ue] rated operational voltage | 48...690 V AC 24...240 V DC |
| [Ith] conventional free air thermal current | 6 A 2.5 A for fault signalling |
| Mechanical durability | 100000 cycles |
| Minimum switching current | 5 mA |
| Minimum switching voltage | 17 V |
| Protection type | GB2CB... circuit breaker GG fuse 10 A |
| Rated operational power in VA | 300 VA 48 V AC-15 100000 cycles 414 VA 690 V AC-15 100000 cycles 500 VA 110...127 V AC-15 100000 cycles 500 VA 500 V AC-15 100000 cycles 650 VA 440 V AC-15 100000 cycles 720 VA 230...240 V AC-15 100000 cycles 850 VA 380...415 V AC-15 100000 cycles 36 VA 24 V AC-14 1000 cycles 48 VA 48 V AC-14 1000 cycles 72 VA 110...127 V AC-14 1000 cycles |
| Rated operational power in W | 120 W 240 V DC-13 100000 cycles 140 W 110 V DC-13 100000 cycles 140 W 24 V DC-13 100000 cycles 180 W 60 V DC-13 100000 cycles 240 W 48 V DC-13 100000 cycles 15 W 48 V DC-13 1000 cycles 24 W 24 V DC-13 1000 cycles 9 W 60 V DC-13 1000 cycles |
| Tightening torque | 12.39 lbf.in (1.4 N.m) screw clamp terminals |
| Height | 3.50 in (89 mm) |
| Width | 0.37 in (9.3 mm) |
| Depth | 2.60 in (66 mm) |
| Net Weight | 0.12 lb(US) (0.055 kg) |
| Color | Dark grey |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|------------------------------|--------------------|
| Environmental characteristic | Normal environment |
| Product Certifications | UKCA |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10I1122367 |
| Discount Schedule | 0I11 |
| GTIN | 3389110343533 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.39 in (1.000 cm) |
| Package 1 Width | 2.76 in (7.000 cm) |
| Package 1 Length | 3.54 in (9.000 cm) |
| Package 1 Weight | 1.48 oz (42.000 g) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 3.74 in (9.500 cm) |
| Package 2 Width | 3.94 in (10.000 cm) |
| Package 2 Length | 5.91 in (15.000 cm) |
| Package 2 Weight | 16.58 oz (470.000 g) |
| Unit Type of Package 3 | S02 |
| Number of Units in Package 3 | 60 |
| Package 3 Height | 5.91 in (15.000 cm) |
| Package 3 Width | 11.81 in (30.000 cm) |
| Package 3 Length | 15.75 in (40.000 cm) |
| Package 3 Weight | 6.87 lb(US) (3.118 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

GVAD0110

