

CUSTOMER: _____

One Signature Required

JOB NAME: _____

PO #: _____ QUOTE # _____

DATE: _____ QUANTITY: L _____ R _____

SHIP TO: _____

PLUMBING CONTRACTOR APPROVAL

____/____/____
DATE

GENERAL CONTRACTOR APPROVAL

____/____/____
DATE

ENGINEER APPROVAL

____/____/____
DATE

ARCHITECT APPROVAL

____/____/____
DATE

To complete your order, this document must be signed and emailed to the Centralized Customer Service Center.

quotes@americanbathgroup.com • 800.443.7269

STANDARD FEATURES

- Pre-leveled base
- Solid Surface
- 1 1/8" skirt
- Compliant when properly installed
- Center front drain outlet
- Integral front trench drain
- 12" x 24" subway tile
- Slip resistant, textured bottom [ASTM F-462]

CONFIGURATION (handed by the seat)

- ☐ Shell reinforced for future accessory installation
 - Seat Wall ☐ LH ☐ RH
 - ☐ Optional vertical bar reinforcement (entry wall)
 - ☐ LH ☐ RH ☐ Both
- ☐ Fully configured with seat — ANSI
 - Seat Wall (must choose one) ☐ LH ☐ RH
 - Includes one stainless steel L-shaped grab bar, one stainless steel vertical 18" grab bar, stainless steel grate and cushioned, white, L-shaped fold-up seat, per ADA guidelines. (std config)
 - ☐ Factory-installed plumbing options per ANSI requirements
 - ☐ Hand-held shower assembly, 30" slide bar and 60" hose
 - ☐ Pressure balancing mixing valve

CUSTOM OPTIONS (not avail. if ANSI configuration is selected)

- Handed by the seat ☐ LH ☐ RH
- ☐ Reinforced for future seat installation
- ☐ L-shaped fold-up seat
 - ☐ Cushioned white ☐ Phenolic teak ☐ Phenolic white
- Horizontal L-shaped grab bars:
 - ☐ Stainless steel (1 1/2" dia.)
 - ☐ Powder-coated white (1 1/4" dia.)
- ☐ Factory-installed plumbing options per ANSI requirements
 - ☐ Hand-held shower assembly, 30" slide bar and 60" hose
 - ☐ Pressure balancing mixing valve
- Grate:
 - ☐ Stainless steel
 - ☐ White


Int. Dim.	36 W x 36 D x 76 3/4 H
Ext. Dim.	42 W x 38 1/8 D x 78 3/4 H
Skirt Ht.	1 1/8 skirt
Packaged Wt.	150 lbs.
Material	Solid Surface
Warranty	30-year warranty*

* See terms and conditions for details

inches

OPTIONAL ACCESSORIES (available for all models)

- ☐ Stainless steel vertical bar 24" x 1 1/2" (entry wall)
 - ☐ LH ☐ RH ☐ Both
- ☐ Large soap dish (12 1/2 W x 3 1/2 D x 1 1/2 H), shipped loose
- ☐ Small soap dish (7 W x 3 1/2 D x 1 1/2 H), shipped loose
- ☐ Curtain rod, shipped loose
- ☐ Shower curtain, shipped loose
- ☐ Brass drain
- Colors:
 - Standard ☐ White
 - ☐ Other (contact customer service for custom color options)
- ☐ Additional accessories: _____



Right hand configuration
shown with optional soap dish


This unit is not suitable for behavioral health applications.



ANSI compliant when fully equipped
and installed according to guidelines.



This unit is not suitable
for behavioral health applications.



FEATURES lbs Dimensional Tolerance $\pm \frac{3}{16}$ ". Dimensions needed for site preparation should be measured from the unit. Manufacturer assumes no responsibility for preparatory work.


Type and Model #	Material	Wall Finish	Pieces	Drain	Dam/Skirt Height	Net Wt.	Pkg. Wt.
Shower SST3838TR 1.125	Solid Surface	Smooth tile	1	Center Front	1 1/8" skirt	140	150

DIMENSIONS

Specifications	inches (mm)
Width: Ext. / Int.	42 / 36
Depth: Ext. / Int.	38 1/8 / 36
Height: Ext. / Int.	78 3/4 / 76 3/4
Enclosure Opening:	36
Skirt Height:	1 1/8
Drain Rough-In (from Back Wall)	32 5/8
Drain Rough-In (from Side Wall)	19 1/8



FRAMING DIMENSIONS inches (mm)

Type	D Depth	W Width	H Height	A	B	C
Alcove	36	38 1/4	—	Box Out	19 1/8	32 5/8



EMAIL TO THE CENTRALIZED CUSTOMER SERVICE CENTER: quotes@americanbathgroup.com

Curtain Rod and Soap Dish Locations (Standard Valve Configuration)



SECTION C-C