

Eaton 30D27R

Catalog Number: 30D27R

Eaton Bussmann series low voltage D fuse, Ultra-rapid, 500V, 30A, Non Indicating, fuse, Class gR, Ultra rapid, Black, Ceramic body



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage D fuse	30D27R
	UPC
	051712605335
EAN	Product Length/Depth
5027590475976	50 mm
Product Height	Product Width
22 mm	22 mm
Product Weight	Compliances
30.32 g	GoST-R
	CE Marked
	RoHS Compliant

Certifications

VDE
IEC 60269
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Type

fuse

Special features

Ultra-rapid

Application

For domestic and general industrial applications

Amperage Rating

30 A

Fuse size

DII

Breaking capacity

50 kA

Construction size (fuse inserts)

DII

Rated voltage AC

500 V

Class

Class gR

Fuse type

D27R - Ultra rapid

Utilization category

gR (general purpose semiconductor protection)

Color

Black

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D2

Construction size

DII

Fuse shape**Brochures**[eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf](#)**Catalogs**[CA134002EN](#)[Bussmann series complete full line catalog no. 1007](#)[30D27R~FUSE-D2 30A F GR 500VAC E27](#)**Compliance information**[UKCA Bottle fuse-links, holders, carriers and accessories](#)[CE Bottle fuse-links, holders, carriers and accessories](#)**Technical data sheets**[4124 D and D0 fuses, bases and accessories](#)

Bottle

Response time

Ultra rapid

Suitable for

E27/DII Fuse base

TFD27 Fuse base screw fixing

SFRD27 Fuse base DIN-Rail mount

TFRD27 Fuse base DIN-Rail mount

Material

White ceramic body

Release characteristic

Super fast (FF)

Quantity

25

Voltage rating

500 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia