

Peregrine

Colors



Gray



Beige



Natural



Mink



Latte



Leather



Spice



Coffee

Size



7" x 48" x 2mm - Luxury Vinyl Tile

- Gray
- Beige
- Natural
- Mink
- Latte
- Leather
- Spice
- Coffee

PEREGRINE



Product Features

Construction	Dimensions	Plank: 7" x 47.98"
	Overall Thickness	2mm
	Wear Layer Thickness	12 mils (0.3mm)
	Raw Material	100% Virgin Vinyl
	Edge Detail	4-Sided Bevel
	Surface	Wood Emboss with Ceramic Bead Finish
Installation Method:	Glue Down	
Recommended Adhesive	TEC Flexera TEC Flexera HT	Bostik LVT-Lock+ Bostik Multi-Lock Bostik Uni-Lock
Warranty	5 Year Commercial / 10 Year Light Commercial / 25 Year Residential Warranty	
Country of Origin	South Korea	

Compliance

Formaldehyde Emission	EN 14041:2004 Pass (Below E1)
Ortho Phthalate Free	Free of DBP, BBP, DEHP, DNOP, DINP, DIDP & DIBP
All flooring products are manufactured in compliance with California and US safety standards.	



Scan for additional
product details



Scan for Product
Specifications

Technical Data

Thickness	EN 428:1993	2.0 +/- 0.15MM
Squareness, Straightness and Length	EN 427:1994	Specification: 152.4 (+/- 0.10)mm *914.4 (+/- 0.50) mm Squareness ≤ 0.25mm
Residual Indentation	EN 433:1994	≤0.1mm
Flexibility	EN 435:1994	Pass
Dimensional Stability	EN 434:1994	≤0.20%
Slip Resistance	EN 13893:2002 / EN 14041	Class DS
Stain Resistance	EN 423:2002 ASTM F 925-02: 2008	Not Affected Average = 0 (No Change)
Resistance to Light	EN 649:1997 = A1:2003	Pass (6 or better)
Reaction to Fire	EN 13501 - 1:2007	Bfl - S1
Flammability	ASTM D2859-06/CPSC FF 1-7	Pass
Fire resistance - CRF	ASTM E648	Class 1
Surface Burning Characteristics	ASTM E84:2010b	Meets Class C Interior Wall & Ceiling Finish Category
Smoke Density	ASTM E 662-06	< 450
Static Load	ASTM F 970	1000 psi: 0.023mm
Effect of Castor Chair	EN 425:2002	Pass
Scratch Resistance	General Industry Standard	≥2500g
Wear Resistance	EN 660-2:1999 + A1:2003	≤0.015g/1000 rotations

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

material
bank



VITL
SURFACES
COMMERCIAL