


Loomed



Colors



White
VTL LDWH



Beige
VTL LDBE



Light Gray
VTL LDLG



Gray
VTL LDGR

Sizes



12" x 24" x 9.5mm

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 24"	11.81" x 23.81"	9.50mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
3" x 24" Bullnose	2.78" x 23.81"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified

Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	> 275 lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	N/A
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	< 0.5%
Certifications	N/A
Country of Origin	USA
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glazed Porcelain



Made in USA



Stock



V2 Slight Variation



DCOF: ≥0.42



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

