

Specifications



Eaton LFI215

Eaton Cooper Power series loadbreak rotatable feedthru insert, EPDM rubber, 15 kV, Phase to ground: 8.3 kV, AC 1 min: 34 kV, DC 15 min: 53 kV, BIL: 95 kV, Corona: 11 kV, 200 A, Individual box kit

General specifications

PRODUCT NAME	Eaton Cooper Power series loadbreak rotatable feedthru insert
CATALOG NUMBER	LFI215
UPC	194006013215
PRODUCT LENGTH/DEPTH	7.1 in
PRODUCT HEIGHT	10.4 in
PRODUCT WIDTH	3.7 in
PRODUCT WEIGHT	5.971 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386

Product specifications

TYPE	Loadbreak rotatable feedthru insert
AC 1 MINUTE VOLTAGE WITHSTAND	34 kV
BASIC IMPULSE LEVEL	95 kV
CURRENT RATING	200 A
DC 15 MINUTE WITHSTAND	53 kV
MATERIAL	EPDM rubber
MAXIMUM RATING PHASE-TO-GROUND	8.3 kV
CORONA VOLTAGE LEVEL - MIN	11 kV
WITH BAIL	Yes
STANDARD VOLTAGE CLASS	15 kV
PACKAGING	Individual box kit

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - LFI215](#)

[Line installation and protective equipment specifiers guide](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

