

Perenne™ is a sophisticated synergy of urban elegance and natural splendor. A harmonious marriage of stone and terrazzo looks with vibrant botanical and geometric deco's. A versatile medley of shapes, sizes, and shades, illustrating the enchanting dance between Mother Nature and modernity. With Perenne, experience the captivating compatibility of organic charm and contemporary innovation.

PERENNE™
Color Body Porcelain





LARGE FORMAT FLOOR / WALL RESIDENTIAL COMMERCIAL INDOOR OUTDOOR

Sugar**

Cookie**

Espresso

Ink

Flour**

Pecan**

Java

Dye

Gray**

Mist**

Amber

Blue

Wynd
(Avail. in 24"x47"*)

Twist
(Avail. in 24"x47"*)

Up

Rhythm

Oblique



Cut Decos can be made with any field tile colors!



Wynd 24x47 Only

Sugar 12x24 & 24x24

Dye 12x24

Sizes												
	47" x 94" 47.09" x 94.49"	47" x 47" 47.09" x 47.09"	24" x 47" 23.50" x 47.09"	24" x 24" 23.50" x 23.50"	12" x 24" 11.81" x 23.62"	18" x 9"	16" x 16"	19" x 19"	1" x 1" 12" x 12" Mesh	3" x 6" 12" x 12" Mesh	3" x 3" 12" x 12" Mesh	2" x 12" SBN
Thickness	6mm	6mm	6mm, 9mm & 2CM	9mm	9mm	9mm	9mm	9mm	9mm	6mm	6mm	6mm & 9mm
Faces	18	18	24	24	24	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Finish	Matte	Matte	Matte & R11	Matte	Matte	Matte	Matte	Matte	Matte	Matte	Matte	Matte
Edge	Rectified	Rectified	Rectified	Rectified	Rectified	Water Cut	Water Cut	Water Cut	Cut	Cut	Cut	Cut
Grout Joint Recommendation												
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating					
Results*	Check Website	Check Website	Check Website	Check Website	Check Website	Check Website	V2					

**AVAILABLE IN SLIM SIZES - 6mm Thickness
24"x47"
47"x47"
47"x94"
47"x110" - TWIST & WYND ONLY

FLOUR, MIST, AND PECAN SLIMS ALSO AVAILABLE IN POLISHED FINISH.

- Sustainability Attributes
- Red List Free
 - Health Product Declaration (HPD) provided upon request
 - Product Packaging is 100% recyclable



Product and Installation Details | ANSI A108.02 Section 4.3.8.2 - For running bond/brick joining patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



*For more information visit www.emser.com.
Always consult a professional for proper usage and installation.