

RSW 500



T-REX® FEROCIOUSLY STRONG® WATERPROOF AND REPAIR TAPE

TYPICAL APPLICATIONS

- For a wide range of indoor and outdoor fixes on a variety of surfaces, including concrete, fabric, metal, plastic, PVC, vinyl, wood and more
- Instantly stops leaks and patches holes

PRODUCT FEATURES

- Most versatile tape for fast fixes
- Flex-to-Fit Technology™ provides maximum stretch around objects for a fiercely tight seal
- Initially repositionable and easy to use with no backing to remove - simply cut, wrap and seal
- Strong adhesive adheres to smooth and rough surfaces including concrete, fabric, metal, plastic, PVC, vinyl, wood and more
- Instantly seals out water, air and moisture and even works under water
- Extreme weather performance in heat, cold, rain and snow in temperatures ranging from -40 F to 240 F
- Made in USA with Global Materials
- 6-month UV resistance
- Meets AAMA 711-22
- Warning: This tape is not designed to withhold water pressure

CONSTRUCTION

Backing: Polyolefin Film

Adhesive: Solventless UV Acrylic Adhesive

STANDARD WIDTHS

1.88 in; 2.83 in
48 mm; 72 mm

STANDARD LENGTH

30 ft
9 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

AAMA 711-22

Tested in accordance with UL 723

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	>24 oz/inch width	>2.63 N/10 mm
Elongation	700%	700%
Service Temperature Range	-40 F to 240 F	-40 C to 116 C
Tensile	>9 lbs/in width	>15.8 N/10 mm
Thickness	10 mil	0.25 mm

Physical and performance characteristics shown above are obtained from tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent product specifications or a guarantee of product performance. Individual rolls may vary from these standards (or physical properties). The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

