



IPL500-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL500-3	3	3.96
IPL500-4	4	5.11
IPL500-5	5	6.25
IPL500-6	6	7.40
IPL500-7	7	8.59
IPL500-8	8	9.69

WIRE ENTRY PORT
WIRE RANGE: 500KCMIL - #4 AWG
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

		POLARIS SALES CO. INC
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED 500 CONNECTOR
<small>DRAWN BY</small> S.PARRY	<small>NAME</small> S.PARRY	<small>DATE</small> 06/2012
<small>MATERIAL:</small> N/A		<small>DWG. NO.</small> IPL500-
<small>SCALE:</small> N/A		<small>SHEET:</small> 1 OF 1