



Overview

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

Main

Product or Component Type	Battery accessory
Number of rack unit	0U
Number of cables	1.0
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide

Batteries & Runtime

Battery Placement	Internal Battery
Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery Voltage	120 V
RBC Quantity	1

Physical

Height	5.51 in (14 cm)
Width	8.27 in (21 cm)
Depth	21.50 in (54.6 cm)
Net Weight	64.15 lb(US) (29.1 kg)
Mounting Mode	Not rack-mountable
USB compatible	No

Conformance

Standards	UL 1778
Product Certifications	CSA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...15000 ft (0.00...4572.00 m)
Storage Relative Humidity	0...95 %

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304218869
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.16 in (38.5 cm)
Package 1 Width	29.53 in (75 cm)
Package 1 Length	11.26 in (28.6 cm)
Package 1 Weight	71.17 lb(US) (32.28 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------