



TECHNICAL INFORMATION



V4 Substantial
Variation



Ready Ship



Recommend
offset pattern
≤33%



DCOF:
≥ 0.42
Matte only



Made in
USA




COLORS



Summit AOT FY02



Contrast AOT FY03




Steely AOT FY04




Summit
3" Landmark Hex
AOT FY02 LANDHEXP




Contrast
3" Landmark Hex
AOT FY03 LANDHEXP




Steely
3" Landmark Hex
AOT FY04 LANDHEXP



Summit 3" Hex
AOT FY02 HEX



Contrast 3" Hex
AOT FY03 HEX



Steely 3" Hex
AOT FY04 HEX

Performance Characteristics

	MATTE	POLISHED
Breaking Strength	>275 lbs	>275 lbs
Chemical Resistance	Resistant	Resistant
DCOF	≥0.42	Not Applicable
Deep Scratch Resistance - Unglazed	Not Applicable	Not Applicable
Frost Resistance	Not Applicable	Not Applicable
Mohs Hardness - EN101	8	6
PEI Rating	Not Applicable	Not Applicable
Water Absorption	<0.5%	<0.5%
Certifications	Not Applicable	Not Applicable
Shade Variation Code	v4	v4

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48"	23.375" x 46.875"	7.94mm	Matte & Polished
12" x 24"	11.625" x 23.375"	7.94mm	Matte & Polished
3" Hex Mosaic	12.125" x 14.625" (sheet size)	7.94mm	Matte
3" Landmark Hex	11.5" x 17" (sheet size)	7.94mm	Polished
3" x 24" Bullnose	3" x 24"		Matte & Polished

* Not all sizes are available in all colors and finish

Please see virginiatile.com for details