

Porto II™ is inspired by the simplistic look of concrete and stone in large format sizes and a range of colors. Available in matte or polished, Porto II is ideal for both residential and commercial spaces.

PORTO II™

Glazed Porcelain



FLOOR / WALL  RESIDENTIAL  COMMERCIAL  INDOOR  OUTDOOR  POOL 



White



Ivory




Fawn



Charcoal**

Mosaics



White








Ivory



Fawn



Charcoal

Sizes	 32" x 32" 31.50" x 31.50"	 24" x 24" 23.62" x 23.62"	 12" x 24" 11.81" x 23.62"	 12" x 12" Mesh 11.69" x 11.69"	 3" x 12" Floor SBN		
Thickness	10mm	8.8mm	8.8mm	8.8mm	8.8mm		
Faces	8	8	10	Random	Random		
Finish	Matte & Polished	Matte & Polished	Matte & Polished	Matte	Matte & Polished		
Edge	Rectified	Rectified	Rectified	Cut	Cut/Rounded		
Grout Joint Recommendation	3/16"	3/16"	3/16"	3/16"	3/16"		
Testing	Abrasion Resistance C1027	Breaking Strength C648	Chemical Resistance C650	Water Absorption C373	DCOF ANSI A1371	Scratch Hardness MOHS	Shade Variation Rating
Results*	III	≥350 lbf	Resistant	≤0.50%	≥0.55 (Matte) ≤0.42 (Polished)	7 (Matte) 5 (Polished)	V3

Polished not recommended for use as commercial or outdoor flooring.

Product and Installation Details | ANSI A108.02 Section 4.3.8.2 - For running bond/brick jointing patterns utilizing tiles (square or rectangular) where the side being offset is greater than 18" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the tile manufacturer. If an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage.



 Sustainability Attributes

- Red List Free
- Health Product Declaration (HPD) provided upon request
- Product Packaging is 100% recyclable
- VOC Free

*For more information visit www.emser.com. Always consult a professional for proper usage and installation.

**Charcoal color not available in 12"x24" polished or 24"x24" polished.