



FIELD TILES		
SIZE	SIZE SPECIFICATIONS	THICKNESS*
<b>UNDULATED TILE</b>		
3"x6"	2.953"x5.905" (75mm x 150mm)	0.366" (9.3mm)
3"x12"	2.953"x11.811" (75mm x 300mm)	0.366" (9.3mm)
<b>TEXTURED TILE</b>		
3"x6" Textured	2.953"x5.905" (75mm x 150mm)	0.366" (9.3mm)
3"x12" Textured	2.953"x11.811" (75mm x 300mm)	0.366" (9.3mm)
3"x6" Waves	2.953"x5.905" (75mm x 150mm)	0.366" (9.3mm)
3"x12" Waves	2.953"x11.811" (75mm x 300mm)	0.366" (9.3mm)

DECORATIVE ACESORIES & FINISHING TOUCHES		
Bar Liner 1"x6"	0.984"x5.905" (25mm x 150mm)	0.669" (17mm)
Bar Liner 1"x12"	0.984"x11.771" (25mm x 299mm)	0.669" (17mm)
Quarter Round 1"x6"	0.905"x5.827" (23mm x 148mm)	0.394" (10mm)
Molding 2.4"x6"	2.401"x5.827" (61mm x 148mm)	1.102" (28mm)
Molding 2.4"x12"	2.401"x11.771" (61mm x 299mm)	1.102" (28mm)
Base Board (Glazed Top Edge) 5.1"x6"	5.157"x5.827" (131mm x 148mm)	0.512" (13mm)
Base Board (Glazed Top Edge) 5.1"x12"	5.118"x11.811" (130mm x 300mm)	0.512" (13mm)

\*Thickness is understood as the highest point of the tile.

APPLICATIONS		
	SUITABLE RESIDENTIAL	SUITABLE COMMERCIAL
Bathroom Walls*	YES	YES
Shower Walls*	YES	YES
Kitchen Walls*	YES	YES
Countertops	NO	NO
Fireplace Surrounds*	YES	YES
Outdoor Cooking / Bar Spaces*	YES	YES
Pool Waterlines / Water Fountains	NO	NO
Floors	NO	NO
TEST METHOD ATSM / ISO		RESULT
Water Absorption	C-373 / 10545-3	Pass
Breaking Strength	C-648 / 10545-4	Pass
Chemical Resistance**	C-651 / 10545-14	Resistant
Facial Dimensions	C-499 / 10545-2	Pass
Range of Thickness	C-499 / 10545-2	Pass
Warpage	C-485 / 10545-2	Pass
INSTALLATION		
GROUT JOINT RECOMMENDATION	SHADE VARIATION	
3/8"	V1 - Uniform Appearance	
CLEANING RECOMMENDATIONS		
Routine with a non-abrasive/non-acidic, mild and PH neutral cleaner		
SEALING GUIDELINES		
Solvent based penetrating sealer suitable for ceramic tiles		
CHARACTERISTICS		
Glaze	Crackle with subtle movement	
Surface Sheen	Semi-Matte	
Texture	Slightly Undulated	

\*Crackle tiles must be properly sealed. (See SEALING instructions in INSTALLATION & MAINTENANCE guidelines) \*\* In order to accomplish this test, the tile must be properly sealed. Due to the nature of our tile, a certain amount of variation in color, shading, surface and texture are to be expected.