

INCANDESCENT/LED 12V HYBRID DECK & PATIO



15070 AZT / 15072 AZT, CO, WHT - MINI STEP LIGHT **15074 AZT - BRICK LIGHT - GLASS LENS / 15073 AZT - LOUVERED**

Description	Designed to be integrated into outdoor steps. Casts a low, even spread of light. Available with louvered or white acrylic faceplate.	Designed to be integrated into brick walls during construction. Casts a low, even spread of light.																																																																				
Ordering Guide & Finish	15070 AZT - Acrylic Lens, Textured Architectural Bronze, Aluminum 15072 AZT - Louvered Lens, Textured Architectural Bronze, Aluminum 15072 CO - Louvered Lens, Copper, Unfinished Copper 15072 WHT - Louvered Lens, Textured White, Aluminum	15074 AZT - Textured Architectural Bronze 15073 AZT - Textured Architectural Bronze																																																																				
Housing	Aluminum or copper faceplate with white reflector. Zinc plated steel housing. White acrylic diffuser on 15070 only	Cast Aluminum with a fully sealed heat-resistant glass lens																																																																				
Lamp Base	12V T5 wedge base socket	(2) 12V T3 bi-pin, high temperature porcelain sockets																																																																				
Supplied Lamp	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X MAX supplied on copper Xenon light source Power usage at 12V AC input VA MAX: 11.6-W(VA)	10-W(VA) Q10T3 (17011) Halogen (2) Halogen light source Power usage at 12V AC input VA MAX: 10-W(VA)																																																																				
Incandescent Lamp Options	6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	N/A																																																																				
LED Lamp Options	2W (18039-13041) see page 159 Compares up to 16W Xenon. Light distribution may be affected by location of sockets.	2W (18042-13044) see page 159 Compares up to 20W Halogen. Light distribution may be affected by location of sockets.																																																																				
Wiring	Wire connection must be made inside fixture housing. 90° supply wire required	Wire connection must be made inside fixture housing. 75° supply wire required																																																																				
Mounting Acces. Included	Mounting hardware and junction box	Stainless steel mounting bracket																																																																				
LED Option	15782 and 15780 - on page 26.	15774 and 15773 - on page 25.																																																																				
Notes	For recessed installation. For outdoor use only	For outdoor use only. Masonry or concrete use only																																																																				
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>15070 Mounting Height</th> <th>0.5'</th> <th>1'</th> <th>1.5'</th> <th>2'</th> <th>2.5'</th> <th>3'</th> <th>3.5'</th> </tr> </thead> <tbody> <tr> <td>6"</td> <td>2.1</td> <td>.5</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12"</td> <td>1.2</td> <td>.98</td> <td>.5</td> <td>.2</td> <td>.1</td> <td>.02</td> <td>-</td> </tr> </tbody> </table>	15070 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	6"	2.1	.5	.1	-	-	-	-	12"	1.2	.98	.5	.2	.1	.02	-	<table border="1"> <thead> <tr> <th>15074 Mounting Height</th> <th>0.5'</th> <th>1'</th> <th>1.5'</th> <th>2'</th> <th>2.5'</th> <th>3'</th> <th>3.5'</th> <th>4'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>.01</td> <td>.04</td> <td>.04</td> <td>-</td> </tr> <tr> <td>24"</td> <td>-</td> <td>-</td> <td>.06</td> <td>.1</td> <td>.09</td> <td>.04</td> <td>.04</td> <td>-</td> </tr> <tr> <td>36"</td> <td>.02</td> <td>.04</td> <td>.04</td> <td>.04</td> <td>.04</td> <td>.04</td> <td>.01</td> <td>-</td> </tr> </tbody> </table>	15074 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	12"	-	-	-	-	.01	.04	.04	-	24"	-	-	.06	.1	.09	.04	.04	-	36"	.02	.04	.04	.04	.04	.04	.01	-								
15070 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'																																																															
6"	2.1	.5	.1	-	-	-	-																																																															
12"	1.2	.98	.5	.2	.1	.02	-																																																															
15074 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'																																																														
12"	-	-	-	-	.01	.04	.04	-																																																														
24"	-	-	.06	.1	.09	.04	.04	-																																																														
36"	.02	.04	.04	.04	.04	.04	.01	-																																																														
	<table border="1"> <thead> <tr> <th>15072 Mounting Height</th> <th>0.5'</th> <th>1'</th> <th>1.5'</th> <th>2'</th> <th>2.5'</th> <th>3'</th> <th>3.5'</th> </tr> </thead> <tbody> <tr> <td>6"</td> <td>2.6</td> <td>.3</td> <td>.09</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12"</td> <td>1.6</td> <td>1.2</td> <td>.54</td> <td>.08</td> <td>.1</td> <td>.04</td> <td>-</td> </tr> </tbody> </table>	15072 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	6"	2.6	.3	.09	-	-	-	-	12"	1.6	1.2	.54	.08	.1	.04	-	<table border="1"> <thead> <tr> <th>15073 Mounting Height</th> <th>0.5'</th> <th>1'</th> <th>1.5'</th> <th>2'</th> <th>2.5'</th> <th>3'</th> <th>3.5'</th> <th>4'</th> <th>4.5'</th> <th>5'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>.3</td> <td>1.1</td> <td>.8</td> <td>.5</td> <td>.1</td> <td>.02</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>-</td> <td>-</td> <td>.1</td> <td>.2</td> <td>.2</td> <td>.2</td> <td>.1</td> <td>.03</td> <td>.02</td> <td>-</td> </tr> <tr> <td>36"</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>.01</td> <td>.01</td> <td>.03</td> <td>.06</td> <td>.03</td> <td>.01</td> </tr> </tbody> </table>	15073 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'	12"	.3	1.1	.8	.5	.1	.02	-	-	-	-	24"	-	-	.1	.2	.2	.2	.1	.03	.02	-	36"	-	-	-	-	.01	.01	.03	.06	.03	.01
15072 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'																																																															
6"	2.6	.3	.09	-	-	-	-																																																															
12"	1.6	1.2	.54	.08	.1	.04	-																																																															
15073 Mounting Height	0.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'																																																												
12"	.3	1.1	.8	.5	.1	.02	-	-	-	-																																																												
24"	-	-	.1	.2	.2	.2	.1	.03	.02	-																																																												
36"	-	-	-	-	.01	.01	.03	.06	.03	.01																																																												

Denotes fixture is compatible with incandescent or LED lamps.