

Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

SECTION 1. IDENTIFICATION

Product name : PURELL® Advanced Hand Sanitizer Soothing Gel

Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron, Ohio 44311

Telephone : 1 (330) 255-6000

Emergency telephone : CHEMTREC 1-800-424-9300

number CHEMTREC +1-703-527-3887: Outside USA & CANADA

Recommended use of the chemical and restrictions on use

Recommended use : Hand Sanitizer

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large

spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information

provided on the package or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Eye irritation : Category 2A

GHS label elements

Hazard pictograms





Signal word : Warning



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Hazard statements : H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

| Chemical name | CAS-No. | Concentration (%) |
|-------------------|---------|-------------------|
| Ethyl Alcohol | 64-17-5 | >= 50 - < 70 |
| Isopropyl Alcohol | 67-63-0 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if irritation develops and persists.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Seek medical advice.

If swallowed, DO NOT induce vomiting.

Rinse mouth with water. Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance.

May form explosive mixtures in air.

Carbon oxides

Hazardous combustion

products

: Carbon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Material can create slippery conditions.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used. Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

Keep in suitable, closed containers for disposal.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Keep away from heat.

Use with local exhaust ventilation.

Avoid contact with eyes.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Keep in properly labelled containers.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Store in accordance with the particular national regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------|---------|-------------------------------------|--|-----------|
| Ethyl Alcohol | 64-17-5 | TWA | 1,000 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,900 mg/m3 | OSHA Z-1 |
| | | STEL | 1,000 ppm | ACGIH |
| Isopropyl Alcohol | 67-63-0 | TWA | 200 ppm | ACGIH |
| | | STEL | 400 ppm | ACGIH |
| | | TWA | 400 ppm 980 mg/m3 | NIOSH REL |
| | | ST | 500 ppm 1,225 mg/m3 | NIOSH REL |
| | | TWA | 400 ppm 980 mg/m3 | OSHA Z-1 |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Samplin g time | Permissible concentratio n | Basis |
|-------------------|---------|--------------------|---------------------|---|----------------------------|--------------|
| Isopropyl Alcohol | 67-63-0 | Acetone | Urine | End of shift at end of workwee | 40 mg/l | ACGIH BEI |



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : No special protective equipment required.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : No special measures necessary provided product is used

correctly.

Protective measures : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Ensure that eye flushing systems and safety showers are

located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with eyes.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, light green

Odour : alcohol-like

Odour Threshold : No data available

pH : 6.5 - 8.5, (20 °C)

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: 76.00 °C

Flash point : 24.00 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids)

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Relative vapour density : No data available

Density : 0.8762 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : No data available

Thermal decomposition : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 3500 - 23000 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Flammable solids

Water-reactive substances

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact

Acute toxicity

Not classified based on available information.

Components:

Ethyl Alcohol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Isopropyl Alcohol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components: Ethyl Alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Isopropyl Alcohol:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethyl Alcohol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

Isopropyl Alcohol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components:

Ethyl Alcohol:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse Result: negative

Isopropyl Alcohol:

Test Type: Buehler Test Exposure routes: Skin contact

Species: Guinea pig



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Method: OECD Test Guideline 406

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethyl Alcohol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Test species: Mouse

Application Route: Ingestion

Result: negative

Isopropyl Alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Test species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Isopropyl Alcohol:

Species: Rat

Application Route: inhalation (vapour)

Exposure time: 104 weeks

Method: OECD Test Guideline 451

Result: negative

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Ethyl Alcohol:



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Isopropyl Alcohol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal

development

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Isopropyl Alcohol:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Ethyl Alcohol: Species: Rat

NOAEL: 2,400 mg/kg

Application Route: Ingestion

Exposure time: 2 y

Isopropyl Alcohol:

Species: Rat NOAEL: 5000 ppm

Application Route: inhalation (vapour)

Exposure time: 104 w

Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 9 d

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h

Isopropyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

Toxicity to bacteria : EC50 (Pseudomonas putida): > 1,050 mg/l

Exposure time: 16 h

Persistence and degradability

Components:

Ethyl Alcohol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Isopropyl Alcohol:

Biodegradability : Result: rapidly degradable

Bioaccumulative potential

Components:

Ethyl Alcohol:

Partition coefficient: n-

: log Pow: -0.35

octanol/water

Isopropyl Alcohol:

Partition coefficient: n-

: log Pow: 0.05

octanol/water

Mobility in soilNo data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. : UN 1987
Proper shipping name : Alcohols, n.o.s.

(Ethanol, Propan-2-ol)

Class : 3
Packing group : III
Packing instruction (cargo : 366

aircraft)

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : UN 1987

Proper shipping name : ALCOHOLS, N.O.S.

(Ethanol, Propan-2-ol)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

National Regulations

49 CFR

UN/ID/NA number : UN 1987
Proper shipping name : Alcohols, n.o.s.

Class : 3
Packing group : III
ERG Code : 127
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Isopropyl Alcohol 67-63-0 3.4086 %

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI

Intermediate or Final VOC's (40 CFR 60.489):

Ethyl Alcohol 64-17-5 65.2821 % Isopropyl Alcohol 67-63-0 3.4086 %

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

| Ethyl Alcohol | 64-17-5 | 50 - 70 % | |
|-------------------|---------|-----------|--|
| Isopropyl Alcohol | 67-63-0 | 1 - 5 % | |

Pennsylvania Right To Know

| Ethyl Alcohol | 64-17-5 | 50 - 70 % |
|-------------------|-----------|-----------|
| Water (Aqua) | 7732-18-5 | 30 - 50 % |
| Isopropyl Alcohol | 67-63-0 | 1 - 5 % |

New Jersey Right To Know

| Ethyl Alcohol | 64-17-5 | 50 - 70 % |
|-------------------|-----------|-----------|
| Water (Aqua) | 7732-18-5 | 30 - 50 % |
| Isopropyl Alcohol | 67-63-0 | 1 - 5 % |

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory



Version 1.1 SDS Number: 400000000693 Revision Date: 10/25/2018

AICS : On the inventory, or in compliance with the inventory

DSL : All components of this product are on the Canadian DSL.

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

| HEALTH | 2 |
|-----------------|---|
| FLAMMABILITY | 3 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Revision Date : 10/25/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.