

Eaton LE215AB04

Catalog Number: LE215AB04

Eaton Cooper Power series loadbreak elbow, 200 A, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:34 kV, DC 15 min:34 kV, Impulse:95 kV, Max corona:11 kV, Test:No, 0.61 inch, 0.97 inch, 15.5 mm, 24.6 mm, #2 AWG, #1 AWG, 20 pack



General specifications

Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LE215AB04
	UPC
	194006008242
Product Length/Depth	Product Height
15.25 in	18 in
Product Width	Product Weight
15.25 in	2.18 lb
Compliances	Certifications
Not Applicable	IEEE 386

defaultTaxonomyAttributeLabel

Type

Loadbreak elbow

AC 1 minute voltage withstand

34 kV

Basic impulse level

95 kV

Cable insulation diameter - max

0.97 in

Cable insulation diameter - min

0.61 in

Solid or compact conductor size

#1 AWG

Stranded or compressed conductor size

#2 AWG

Current rating

200 A

DC 15 minute withstand

34 kV

Maximum rating phase-to-ground

8.3 kV

Corona voltage level - min

11 kV

Standard pack

20 pack

Standard voltage class

15 kV

Resources

Specifications and datasheets

[Eaton Specification Sheet - LE215AB04](#)

[Line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia