


## **QX530QT DATA SHEET**

## TECHNICAL SPECIFICATIONS



3.875" (98.42mm) Mounting Depth

**Bottom View** 

SKU
Tweeter

Woofer
Frequency Response
Nominal Impedance

Recommended Power Range Sensitivity (2.83V/1m) Crossover

Average Coverage Angle

Finishes

Cut-Out Dims (WxH)

Required Mounting Depth (D) Overall Dimensions (WxHxD)

Grille Dimensions (WxH)
Environment

QX530QT

60645 - Each

Quadratech 0.75" (19mm) four titanium dome Tweeter, Ferrofluid-cooled

(2) 5.25" (127mm) Aluminum

68Hz-24kHz +/-3dB

4 ohms

50 watts minimum; 200 watts maximum

90dB SPL

2-way

106 Degrees Horizontal; 65 Degrees

Vertica

Aircraft Marine Grade Aluminum

White Paintable Grille (Paintable By

Request Only)

7.125" x 20.7" (180.98mm x 525.78mm)

3.875" (98.42mm)

7.75" x 21.325" x 4.125"

(196.85mm x 541.65mm x 104.77mm)

7.75" x 21.325" (196.85mm x 541.65mm)

For indoor use: Available as Marine Grade.

must specify when ordering

## QX530QT IN-WALL ACCESSORIES

QX530PB

Steel Pre Construction Board | 60179

QX530PBF

MDF Flush-Mount Pre Construction Board | 60178

James by Sonance warrants this product to the original purchaser to be free from defects in materials and workmanship under normal use. Limited Lifetime Warranty applies to indoor installations. Limited Five (5) Year Warranty applies to outdoor or moisture-dense environments (e.g., spas, showers, saunas). Grille is warranted for five (5) years for both indoor and outdoor use. Warranty valid only for products purchased from authorized dealers and installed per manufacturer guidelines. Excludes damage from misuse, accidents, modifications, improper installation, or normal wear. For details or claims, visit sonance.com/company/contact