

Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8502 type SE contactor[RETURN]Class 8903 type SQ lighting contactor[RETURN]Class 8910 type DPA12/SYD138 contactor

Complementary

NEMA size	3
[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	700 VA 678 VA
Average consumption	46 VA 47 VA
Height	2.9 in (73 mm)
Width	2.6 in (65 mm)
Depth	0.082 in (2.093 mm)

Ordering and shipping details

Category	US1CP1018079
Discount Schedule	CP10
GTIN	785901110903
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.10 in (5.334 cm)
Package 1 Width	2.80 in (7.112 cm)
Package 1 Length	3.40 in (8.636 cm)
Package 1 Weight	13.440 oz (381.017 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	3.10 in (7.874 cm)
Package 2 Width	4.20 in (10.668 cm)
Package 2 Length	13.10 in (33.274 cm)
Package 2 Weight	17.209 lb(US) (7.806 kg)

Offer Sustainability

Packaging without single use plastic	No
Packaging made with recycled cardboard	No
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Circularity Profile	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty	18 months
----------	-----------