E-SPOT® LITEBOX®
RECHARGEABLE LANTERN



Case Material:	High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle
Dims/Weight:	Length: 11.5 in. (29.2 cm) Width: 5.1 in. (13 cm) Height: 7 in. (17.8 cm) 7.9 lbs (3.58 kg) with battery (included in purchase)
Light Source:	3 shockproof C4® LEDs with a 50,000 hour lifetime. Jumper selectable high or low settings allow selection of more light output or more runtime
Output:	User selectable high or low setting to allow higher light output or longer run time: - High: 540 lumens; 55,000 candela; 469m beam; runs 7 hours - Low: 330 lumens; 32,000 candela; 358m beam; runs 15 hours
Battery:	Zero-maintenance 6V, 12Ah sealed lead acid battery. Red and green LEDs give charge status feedback
Models:	Standard System - International safety orange or high-visibility yellow; includes shoulder strap; includes AC/DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites, and remote equipment. Vehicle Mount System - International safety orange or high-visibility yellow; includes vehicle-mountable hard-wire rack and shoulder strap. Power Failure System - International safety orange or beige; includes AC/DC chargers and "smart" power failure circuitry that automatically illuminates the E-Spot LiteBox when the power is lost
Approvals:	Most models meet applicable European Community Directives. Charge rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position.
Warranty:	Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
E-Spot LiteBox Standard System - IEC Type A (120V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45851-2	45851
E-Spot LiteBox Standard System - IEC Type A (100V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45854-3	45854
E-Spot LiteBox Standard System - IEC Type C (230V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45852-9	45852
E-Spot LiteBox Standard System - IEC Type G (240V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45853-6	45853
E-Spot LiteBox Standard System - IEC Type A (120V) AC/12V DC charge cords, shoulder strap & mounting rack - Yellow	080926-45871-0	45871
E-Spot LiteBox Standard System - IEC Type A (100V) AC/12V DC, shoulder strap & mounting rack - Yellow	080926-45874-1	45874
E-Spot LiteBox Standard System - IEC Type C (230V) AC/12V DC charge cords, shoulder strap & mounting rack - Yellow	080926-45872-7	45872
E-Spot LiteBox Standard System - IEC Type G (240V) AC/12V DC charge cords, shoulder strap & mounting rack - Yellow	080926-45873-4	45873
E-Spot LiteBox Vehicle Mount System - 12V DC direct wire rack - Orange	080926-45855-0	45855
E-Spot LiteBox Vehicle Mount System - 12V DC charge cord and DC direct wire rack - Yellow	080926-45875-8	45875
E-Spot LiteBox Power Failure System - IEC Type A (120V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45857-4	45857
E-Spot LiteBox Power Failure System - IEC Type A (100V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45860-4	45860
E-Spot LiteBox Power Failure System - IEC Type C (230V) AC/12V DC charge cords, shoulder strap & mounting rack - Orange	080926-45858-1	45858
E-Spot LiteBox Power Failure System - IEC Type G (240V) AC/12V DC charge cords, shoulder strap & mounting rack - Orange	080926-45859-8	45859
E-Spot LiteBox Power Failure System - IEC Type A (120V) AC/12V DC charge cords, shoulder strap & mounting rack - Beige	080926-45867-3	45867
E-Spot LiteBox Power Failure System - IEC Type C (100V) AC/12V DC, shoulder strap & mounting rack - Beige	080926-45870-3	45870
E-Spot LiteBox Power Failure System - IEC Type C (230V) AC/12V DC charge cords, shoulder strap & mounting rack - Beige	080926-45868-0	45868
E-Spot LiteBox Power Failure System - IEC Type G (240V) AC/12V DC charge cords, shoulder strap & mounting rack - Beige	080926-45869-7	45869
E-Spot LiteBox (WITHOUT CHARGER) Orange	080926-45856-7	45856
E-Spot LiteBox (WITHOUT CHARGER) Power Failure - Beige	080926-45866-6	45866
E-Spot LiteBox (WITHOUT CHARGER) Yellow	080926-45876-5	45876



#22060



#40163



#45072
#45074



#45070
#45071



#45073



#22061



#22062



#45845



#45937



#22051



#22050



#44050

Item		UPC	Part #
DC2 direct wire charge cord		080926-22050-8	22050
DC1 Charge Cord		080926-22051-5	22051
IEC Type C (230V) AC charge cord		080926-22061-4	22061
IEC Type A (100V/120V) AC charge cord		080926-22060-7	22060
IEC Type G (240V) AC charge cord		080926-22062-1	22062
*Locking Device (keyed differently) *Must be factory installed*		080926-40163-1	40163
Quick Release Strap		080926-44050-0	44050
Shoulder Strap		080926-45232-9	45232
Standard System Mounting Rack	Orange	080926-45070-7	45070
Direct Wire 12V DC Mounting Rack	Orange	080926-45071-4	45071
Standard System Mounting Rack	Yellow	080926-45072-1	45072
Direct Wire 12V DC Mounting Rack	Yellow	080926-45074-5	45074
Mounting Rack (LiteBox)	Beige	080926-45073-8	45073
Sealed Lead Acid Battery		080926-45937-3	45937
E-Spot Upgrade Kit		080926-45845-1	45845

STREAMLIGHT

30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
www.streamlight.com ©Streamlight E-Spot LiteBox 2/17