

DS-K7M151-P

Clamshell Proximity Card



- 125 kHz Frequency
- Slot-Punched Standard Vertical Slot
- Up to 8" Read Range (202 mm)
- 25 Clamshell Cards Included

Hikvision proximity cards set the electronic security benchmark for 125 kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, proximity readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol.

Additionally, proximity cards and tags are passive devices and eliminate the need for maintenance by requiring no batteries, and can be ordered to support several proximity reader technologies.

Available Models:

DS-K7M151-P

Specifications

DS-K7M151-P	
System Parameters	
Technology	Proximity
Frequency	125 kHz
Operation	Passive (no battery)
Type	Clamshell card
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	ABS
Color	Off-white
Slot Punch	Standard, vertical slot
Marking	Date code and ID
Read Range	Up to 8" (202 mm)
Single Clamshell Card Dimensions	2.2" W x 3.4" H x 0.06" D (56 mm x 86 mm x 1.5 mm)
Shipping Dimensions (25 Clamshell Cards)	3.5" W x 2.3" H x 1.8" D (88 mm x 57 mm x 46.8 mm)
Weight	Single clamshell card: 0.3 oz (9 g) Box of 25 clamshell cards 0.6 lbs (272 g)
Operating Temperature	-35° to 122° F (-37° to 50° C)
Humidity	0% to 95% (non-condensing)