

Cleerline™ Outdoor Plastic Enclosures provide secure protection for terminations in OSP environments. Each plastic enclosure is designed to maximize efficiency, allowing easy access to feed-thru adapters while using the least amount of space possible.

These enclosures provide ample cable management, including winding areas and pass through. Hinged internal distribution panels allow two levels of cable management.

Cleerline™ Outdoor Plastic Enclosures are available in sizes to accommodate 2, 4, or 12 feed-thru's.

FEATURES AND BENEFITS

- Durable plastic construction
- Included winding area
- Compatible with standard adapters for fiber optic connectors
- Secure closure
- Optimized cable management
- PC + ABS material, waterproof, dust-proof, protection up to IP65



Adapters Are Not Included

ENVIRONMENTAL REQUIREMENTS

Working Temperature	-40°C - +85°C
Relative Humidity	< 85% (+30°C)
Atmospheric Pressure	70 kPa - 106 kPa

SPECIFICATIONS

Part Number	SSF-OTB2	SSF-OTB4	SSF-OTB12
Feed-Thru Capacity	2	4	12
Height	6.5 in / 16.5 cm	7.3 in / 18.6 cm	8.89 in / 22.6 cm
Width	4.75 in / 12.1 cm	4.6 in / 11.6 cm	8.38 in / 21.3 cm
Depth	1.19 in / 3.0 cm	1.57 in / 4.0 cm	2.63 in / 6.7 cm

PART NUMBER	DESCRIPTION
SSF-OTB2	Outdoor Fiber Optic Terminal box, Empty (Holds 2 SC Simplex or 2 LC Duplex Adapters)
SSF-OTB4	Outdoor Fiber Optic Terminal box, Empty (Holds 4 SC Simplex or 4 LC Duplex Adapters)
SSF-OTB12	Outdoor Fiber Optic Terminal box, Empty (Holds 12 SC Simplex or 12 LC Duplex Adapters)