

**Outdoor**

**HALO Outdoor**  
Residential & Light  
Commercial



# FE LED Entry Light

## HALO Outdoor

The HALO FE Outdoor entry and patio light is an affordable, low-maintenance and reliable security solution that provides nighttime ON and daytime OFF settings. Suitable for mounting heights up to 10 ft., the entry light is ideal for residential applications such as entrances, patios, walkways, apartment complexes and light commercial buildings such as outlet exteriors, doorways, storage areas and hotels.



FE0650LPCW



FE0650LPC



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
FE0650LPC	Entry with Integral PC	Bronze	75W INC	5000K	811	9	120V	240	080083803644
FE0650LPCW	Entry with Integral PC	White	75W INC	5000K	927	9	120V	240	080083808830

# FSS/FSL LED Floodlight

## HALO Outdoor

The FSS/FSL LED single-head floodlights feature three selectable color temperatures that can be chosen in the field during or after installation. The security lights provide superior area coverage with wattage equivalents ranging from 150W to 500W incandescent. The series features a rugged die-cast aluminum housing with precision optics and an optically enhanced reflector for improved efficiency and light output of up to 5,800 lumens. The floodlights include an optional integrated dusk-to-dawn photocontrol for nighttime ON and daytime OFF capability. Designed for either wall or eave mounting, the floodlights are easy to install and feature tool-less head adjustment.



Catalog Number	Product Description	Finish	Replaces Up To	Selectable CCT	Lumens (up to)	Watts	Voltage	Pallet Quantity	UPC
FSS153TIB	Small Single with PC	Bronze	150W INC	3000K, 4000K, 5000K	1,503	17	120V	336	080083809851
FSS153TIW	Small Single with PC	White	150W INC	3000K, 4000K, 5000K	1,503	17	120V	336	080083809974
FSL203TB	Large Single	Bronze	180W INC	3000K, 4000K, 5000K	1,916	23	120-277V	252	080083809677
FSL203TW	Large Single	White	180W INC	3000K, 4000K, 5000K	1,916	23	120-277V	252	080083809738
FSL203TIB	Large Single with PC	Bronze	180W INC	3000K, 4000K, 5000K	1,916	23	120V	252	080083809691
FSL303TB	Large, Single High Output	Bronze	280W INC	3000K, 4000K, 5000K	2,900	32	120-277V	252	080083809752
FSL303TIB	Large Single, High Output with PC	Bronze	280W INC	3000K, 4000K, 5000K	2,900	32	120V	150	080083809776
FSL303TW	Large Single, High Output	White	280W INC	3000K, 4000K, 5000K	2,900	32	120-277V	150	080083809813
FSL503TIB	Large Single with PC	Bronze	500W INC	3000K, 4000K, 5000K	5,800	52	120-277V	96	080083809851
FSL503TB	Large Single	Bronze	500W INC	3000K, 4000K, 5000K	5,800	52	120-277V	96	080083867110
FSL503TIW	Large Single with PC	White	500W INC	3000K, 4000K, 5000K	5,800	52	120-277V	96	080083867134
FSL503TW	Large Single	White	500W INC	3000K, 4000K, 5000K	5,800	52	120-277V	96	080083867158

Outdoor

Residential & Light Commercial

# FHS LED Floodlight

HALO Outdoor

The LED triple-head floodlights feature three selectable color temperatures that can be chosen in the field during or after installation. Providing superior area coverage equivalent to 280W incandescent, the series features rugged die-cast aluminum housings with precision optics and optically enhanced reflectors for improved efficiency and light output over 2,850 lumens. Wall or eave mounting, the versatile floodlight is easy to install and feature tool-less head adjustment.



Catalog Number	Product Description	Finish	Replaces Up To	Selectable CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
FHS303TW	Small Triple	White	280W INC	3000K, 4000K, 5000K	2,853	32	120-277V	144	080083810413

# FTR LED Floodlight

HALO Outdoor

The HALO Outdoor FTR LED twin-head round flood fixtures with photocontrol utilize LED technology to maximum light output in a low-profile, compact housing. This design is ideal as a direct replacement for traditional style floodlights and is suitable for eave or wall mounting.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Watts	Voltage	Pallet Quantity	UPC
FTR1740LPC	Twin Round	Bronze	2-75W, PAR 38	5000K	20.5	120V	140	080083810413

# PC LED Twin Floodlight

HALO Outdoor

The PC LED twin head flood series is ideal in outdoor areas where a low-maintenance solution is required. Producing either 1,300 or 2200 lumens, this compact floodlight can be wall or eave mounted for maximum versatility. Upon installation, choose between one of 3 color temperatures: 3000K (soft white), 4000K (bright white), or 5000K (daylight). This outdoor rated product utilizes a durable rust free polycarbonate housing. Available in Flood, Dusk-to-Dawn, or Motion activated models.



Catalog Number	Product Description	Finish	Replaces Up To	Selectable CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
FT18VCB	Twin head floodlight	Bronze	90W INC	3000K, 4000K, 5000K	1,300	13	120V	288	080083837090
FT18VCW	Twin head floodlight	White	90W INC	3000K, 4000K, 5000K	1,300	13	120V	288	080083837151
FT18VCIB	Twin head floodlight with PC	Bronze	90W INC	3000K, 4000K, 5000K	1,300	13	120V	288	080083837113
FT18VCIW	Twin head floodlight with PC	White	90W INC	3000K, 4000K, 5000K	1,300	13	120V	288	080083837137
FT28VCB	Twin head floodlight	Bronze	180W INC	3000K, 4000K, 5000K	2,200	20	120V	288	080083837175
FT28VCW	Twin head floodlight	White	180W INC	3000K, 4000K, 5000K	2,200	20	120V	288	080083837212
FT28VCIB	Twin head floodlight with PC	Bronze	180W INC	3000K, 4000K, 5000K	2,200	20	120V	288	080083840168
FT28VCIW	Twin head floodlight with PC	White	180W INC	3000K, 4000K, 5000K	2,200	20	120V	288	080083837199
MST18VCB	Twin head floodlight, 180° PIR	Bronze	90W INC	3000K, 4000K, 5000K	1,300	13	120V	120	080083837236
MST18VCW	Twin head floodlight, 180° PIR	White	90W INC	3000K, 4000K, 5000K	1,300	13	120V	120	080083837250
MST28VCB	Twin head floodlight, 180° PIR	Bronze	180W INC	3000K, 4000K, 5000K	2,200	20	120V	120	080083837274
MST28VCW	Twin head floodlight, 180° PIR	White	180W INC	3000K, 4000K, 5000K	2,200	20	120V	120	080083837298

# MSS LED Motion Floodlight

HALO Outdoor

The LED single-head, 180° motion-activated floodlights are designed with advanced two-stage LED optics, providing superior area coverage equivalent to 150W incandescent, producing light output over 1,500 lumens. Three selectable color temperatures can be chosen in the field during or after installation. The floodlight features a rugged die-cast aluminum housing with a UV stable, polycarbonate clear lens that can be wall or eave mounted.



Catalog Number	Product Description	Finish	Replaces Up To	Selectable CCT	Voltage	Lumens	Watts	Pallet Quantity	UPC
MSS153T18B	Single, 180° PIR	Bronze	150W INC	3000K, 4000K, 5000K	120V	1,503	17	336	080083808908
MSS153T18W	Single, 180° PIR	White	150W INC	3000K, 4000K, 5000K	120V	1,503	17	336	080083810369

# MST LED Motion Floodlight

HALO Outdoor

The LED twin-head, 180° or 280° motion-activated floodlight series is designed with the latest advanced LED technology, providing superior area coverage equivalent to 180W incandescent. The floodlights include an integrated photocontrol to ensure lights only come on after dark and an adjustable detection area motion sensor, which automatically turns lights on when motion is detected (up to 50 feet) and off after a preselected time delay. The series features three selectable color temperatures that can be chosen in the field during or after installation.



Catalog Number	Product Description	Finish	Replaces Up To	Selectable CCT	Lumens (up to)	Watts	Voltage	Pallet Quantity	UPC
MST203T18B	Twin, 180° PIR	Bronze	180W INC	3000K, 4000K, 5000K	2,034	23	120V	192	080083810161
MST203T18W	Twin, 180° PIR	White	180W INC	3000K, 4000K, 5000K	2,034	23	120V	192	080083810185
MST203T27B	Twin, 270° PIR	Bronze	180W INC	3000K, 4000K, 5000K	2,034	23	120V	192	080083810246

## AL30 LED Area/Site

HALO Outdoor

The AL30 LED area and wall light combines advanced LED technology with rugged construction and integrated dusk-to-dawn photocontrol for nighttime ON and daytime OFF capability. Offering an energy efficient and reliable security solution, the series provides energy savings of up to 90% versus traditional light sources and is ideal for illuminating large areas including side roads, pathways, barns and other security lighting applications.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
AL3050LPCGY	LED Area Light, Integrated PC	Gray	100W HID; 65W CFL	5000K	3,300	34	120V	48	080083709977

## AL75 LED Area/Site

HALO Outdoor

The HALO AL7550 LED area light combines a low design with a powerful punch. At 8100 lumens this fixture provides enough light for large areas such as parking lots, roadways, barns, as well as other commercial grade applications. The rugged, yet sleek, die cast construction includes a twist lock dusk to dawn photocontrol for nighttime ON and daytime OFF functionality for maximum energy savings while still delivering reliable security lighting.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
AL7550LPCBZ	LED Area Light, 3-Pin NEMA photocell	Bronze	175W MH	5000K	8,100	62	120-277V	100	080083837076
AL7550LPCGY	LED Area Light, 3-Pin NEMA photocell	Gray	175W MH	5000K	8,100	62	120-277V	100	080083837052

## AL48 LED Area/Site

HALO Outdoor

The Halo AL4850 LED bronze area light provides superior performance with the added feature of minimal uplight (wasted light in the sky). Using state of the art technology, the AL4850 removes the need for a drop lens, while still maintaining broad area coverage. Rugged construction includes a dusk to dawn photocontrol for nighttime ON and daytime OFF functionality, which provides a reliable security solution.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
AL4850LPCGY	LED Area Light, Integrated PC	Gray	150W MH	5000K	5444	42	120V	60	080083837014
AL4850LPCBZ	LED Area Light, Integrated PC	Bronze	150W MH	5000K	5444	42	120V	60	080083837038



**Outdoor**

**Lumark**  
Commercial & Industrial



# Axcent LED Wall Mount Luminaire

Lumark

The Axcent LED wall mount luminaire provides a flush-mounted, architectural design with high-performing, energy-efficient illumination. The die-cast aluminum construction along with stainless steel hardware, gasketed housing, and sealed optical compartment makes the Axcent impervious to contaminants. Ideal for building entrances, vehicle ramps, schools, tunnels, stairways, loading docks, and floodlighting applications.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
AXCS1A	Small Full Cutoff	Carbon Bronze	70W HID	4000K	1,806	14	120-277V	96	080083887965	PM2QBCKN, P6C9PUNY
AXCS1ARL	Small Refractive Lens	Carbon Bronze	70W HID	4000K	1,915	14	120-277V	96	080083887972	PHYZYQ8H, PUMEIQIOG
AXCS2A	Small Full Cutoff	Carbon Bronze	100W HID	4000K	2,561	21	120-277V	96	080083887989	P7QPNUH6, PSBR7D60
AXCS2ARL	Small Refractive Lens	Carbon Bronze	100W HID	4000K	2,716	21	120-277V	96	080083887996	PTRCMYKE, PSC2T7M7
AXCS3A	Small Full Cutoff	Carbon Bronze	150W HID	4000K	3,537	27	120-277V	96	080083888009	PVRJ2Q9Q, PTFQ0X79
AXCS3ARL	Small Refractive Lens	Carbon Bronze	150W HID	4000K	3,704	27	120-277V	96	080083888016	PZQJ7RFY, PMU3T43Q
AXCS4A	Small Full Cutoff	Carbon Bronze	250W HID	4000K	5,520	44	120-277V	96	080083888023	PI16J9UO, POMJ1T2K
AXCS4ARL	Small Refractive Lens	Carbon Bronze	250W HID	4000K	5,858	44	120-277V	96	080083888030	PPXSGJ9K, PCFKRFBV
AXCS5A	Small Full Cutoff	Carbon Bronze	320W HID	4000K	6,300	52	120-277V	96	080083888047	PHKFITX6, PCPDYSZM
AXCS5ARL	Small Refractive Lens	Carbon Bronze	320W HID	4000K	6,699	52	120-277V	96	080083888054	PUKEBS4Y, PMOJUK2F
AXCL6A	Large Full Cutoff	Carbon Bronze	320W HID	4000K	7,594	56	120-277V	45	080083811564	PVMFE6IH
AXCL6ARL	Large Refractive Lens	Carbon Bronze	320W HID	4000K	7,809	56	120-277V	45	080083811649	PZXNXUOI
AXCL8A	Large Full Cutoff	Carbon Bronze	400W HID	4000K	9,696	72	120-277V	45	080083811588	PG4TJNY3
AXCL8ARL	Large Refractive Lens	Carbon Bronze	400W HID	4000K	9,970	72	120-277V	45	080083811663	PBA84MB6
AXCL10A	Large Full Cutoff	Carbon Bronze	400W HID	4000K	13,283	102	120-277V	45	080083811601	PEEEJWAF
AXCL10ARL	Large Refractive Lens	Carbon Bronze	400W HID	4000K	13,641	102	120-277V	45	080083811687	PJAMFHC, PDOZ54B9
AXCL12A	Large Full Cutoff	Carbon Bronze	450W HID	4000K	16,823	123	120-277V	45	080083811625	PD1N4D39
AXCL12ARL	Large Refractive Lens	Carbon Bronze	450W HID	4000K	17,346	123	120-277V	45	080083811700	PYCDCLQY, PWOPA823

# Crosstour LED Wall Pack

Lumark

The Crosstour LED wall pack series provides an architectural style with super bright, energy-efficient LEDs. The Crosstour series features low-profile, rugged die-cast aluminum construction, universal back box, stainless steel hardware along with a sealed and gasketed optical compartment, making the product impervious to contaminants. The wall luminaire is ideal for surface or inverted mount for facade/canopy illumination, post/bollard mounting and for low level pathway illumination including stairs. Typical applications include building entrances, multi-use facilities, apartment buildings, institutions, schools, stairways and loading docks.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
XTOR1B	Small Full Cutoff	Carbon Bronze	70W HID	5000K	1,418	12	120-277V	240	080083777969	PRVAZAZR
XTOR2B	Small Full Cutoff	Carbon Bronze	100W HID	5000K	2,135	18	120-277V	270	080083778225	PGP4FVY3
XTOR3B	Small Full Cutoff	Carbon Bronze	150W HID	5000K	2,751	26	120-277V	270	080083778041	PWFZHYJH
XTOR4B	Medium Full Cutoff	Carbon Bronze	250W HID	5000K	4,269	38	120-277V	270	080083778003	PUJ1NXGY
XTOR6B	Large Full Cutoff	Carbon Bronze	320W HID	5000K	6,129	58	120-277V	60	080083774807	PWEKQNMV
XTOR6BRL	Large Refractive Lens	Carbon Bronze	320W HID	5000K	6,225	58	120-277V	60	080083774821	PH59ANRG
XTOR8B	Large Full Cutoff	Carbon Bronze	400W HID	5000K	8,502	81	120-277V	60	080083774814	P5557CRH
XTOR8BRL	Large Refractive Lens	Carbon Bronze	400W HID	5000K	8,635	81	120-277V	60	080083774852	P2F72ZQT



## WP LED Glass Wall Pack

Lumark

The WP wall pack luminaire provides traditional architectural style with high performance energy efficient illumination. Rugged die-cast aluminum construction, stainless steel hardware along with a sealed and gasketed optical compartment make it virtually impenetrable to contaminants. The WP LED wall luminaire is ideal for pathway illumination, building entrances, vehicle ramps, schools, tunnels, stairways and loading docks.



WPSLED



WPMLED



WPLLED



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
WPSLED-30-GL-UNV	Small Refractive Lens	Bronze	150W HID	4000K	3,382	27	120-277V	26	080083776368	PZ4PQJ7J
WPSLED-30-GL-UNV-PC	Small Refractive Lens, PC	Bronze	150W HID	4000K	3,382	27	120-277V	26	080083776528	
WPSLED-30-GL-UNV-7050	Small Refractive Lens	Bronze	150W HID	5000K	3,435	27	120-277V	26	080083776443	P2WTNDW5
WPMLED-75-GL-UNV	Medium Refractive Lens	Bronze	320W HID	4000K	8,683	76	120-277V	72	080083776382	PAGM5GGQ
WPMLED-75-GL-UNV-PC	Medium Refractive Lens, PC	Bronze	320W HID	4000K	8,683	76	120-277V	72	080083776542	
WPMLED-75-GL-UNV-7050	Medium Refractive Lens	Bronze	320W HID	5000K	8,818	76	120-277V	72	080083776467	PBFHFR3H
WPLLED-100-GL-UNV	Large Refractive Lens	Bronze	400W HID	4000K	10,264	82	120-277V	48	080083776405	P6V82M4V
WPLLED-100-GL-UNV-PC	Large Refractive Lens, PC	Bronze	400W HID	4000K	10,264	82	120-277V	48	080083776566	
WPLLED-100-GL-UNV-7050	Large Refractive Lens	Bronze	400W HID	5000K	10,424	82	120-277V	48	080083776481	P2SXNNP1
WPLLED-125-GL-UNV	Large Refractive Lens	Bronze	450W HID	4000K	15,143	122	120-277V	40	080083776429	PGDAEG6T
WPLLED-125-GL-UNV-PC	Large Refractive Lens, PC	Bronze	450W HID	4000K	15,143	122	120-277V	40	080083776580	
WPLLED-125-GL-UNV-7050	Large Refractive Lens	Bronze	450W HID	5000K	15,379	122	120-277V	40	080083776504	PAKFM3BD

## WPSQLED LED Glass Wall Pack

Lumark

The WPSQLED wall-mount luminaire provides a traditional square style with high performance and energy-efficient illumination, resulting in up to 84% energy and maintenance savings over traditional MH luminaires. The rugged, die-cast aluminum construction is IP66 rated and UL/cUL wet location listed for exceptional durability and long term reliability. With lumen maintenance greater than 91% at 60,000 hours, the WPSQLED luminaire is virtually maintenance free. Replacing up to 450W MH equivalent luminaires, the WPSQLED luminaire is ideal for pathway illumination, building entrances, vehicle ramps, schools, tunnels, stairways and loading docks.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
WPSQLED-65-UNV	Large Refractive Lens	Bronze	175W HID	4000K	7,108	64	120-277V	16	080083805662	PL5JKA2T2HJF
WPSQLED-65-UNV-7050	Large Refractive Lens	Bronze	175W HID	5000K	7,446	64	120-277V	16	080083805723	PLKVZN8V8BCZ
WPSQLED-65-UNV-PC	Large Refractive Lens, PC	Bronze	175W HID	4000K	7,108	64	120-277V	16	080083805907	PL5JKA2T2HJF
WPSQLED-75-UNV	Large Refractive Lens	Bronze	250W HID	4000K	7,706	75	120-277V	16	080083805686	PL88EYZWS38V
WPSQLED-75-UNV-7050	Large Refractive Lens	Bronze	250W HID	5000K	7,918	75	120-277V	16	080083805747	PL000UAIGOSF
WPSQLED-75-UNV-PC	Large Refractive Lens, PC	Bronze	250W HID	4000K	7,706	75	120-277V	16	080083805921	PL88EYZWS38V
WPSQLED-100-UNV	Large Refractive Lens	Bronze	320-450W HID	4000K	11,043	101	120-277V	16	080083805709	PL9CZYJ28FAY
WPSQLED-100-UNV-7050	Large Refractive Lens	Bronze	320-450W HID	5000K	11,322	101	120-277V	16	080083805761	PLIM3WU8Z79W
WPSQLED-100-UNV-PC	Large Refractive Lens, PC	Bronze	320-450W HID	4000K	11,043	101	120-277V	16	080083805945	PL9CZYJ28FAY

# LVL Vaportight

Lumark

The LVL LED Vaportight area luminaire provides an indoor/outdoor solution in applications where lighting fixture protection against dust and moisture is required. This fixture's traditional look and warm color temperature delivers visual comfort. The fixture is ideal for industrial and decorative residential uses including patio, garages and storage.



Catalog Number	Product Description	Finish	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC
LVL20UG	Round, Cage Lens, Ceiling/Wall/Post Mount	Grey	3500K	1,450	18	120/277V	256	080083803637

# CLCSLED Canopy

Lumark

The CLCSLED canopy luminaire provides a slim, low-profile, traditional design with high-performance, energy-efficient illumination. The CLCSLED luminaire seamlessly integrates into new or existing spaces including bank drive-thrus, covered side walks, hospitality entryways and retail drive-thrus.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
CLCSLED-40-SM-UNV	Square Surface Mount	Bronze	150W HID	4000K	4,839	36	120-277V	144	080083776061	PCQT436Y
CLCSLED-40-SM-UNV-7050	Square Surface Mount	Bronze	150W HID	5000K	4,739	36	120-277V	144	080083776184	PSDWDZ8R
CLCSLED-40-SM-UNV-BPC	Square Surface Mount	Bronze	150W HID	4000K	4,839	36	120-277V	16	080083776269	
CLCSLED-55-SM-UNV	Square Surface Mount	Bronze	175W HID	4000K	7,230	56	120-277V	144	080083776085	PJ1SCY7M
CLCSLED-55-SM-UNV-7050	Square Surface Mount	Bronze	175W HID	5000K	6,878	56	120-277V	144	080083776207	PMYBEAJZ
CLCSLED-55-SM-UNV-BPC	Square Surface Mount, PC	Bronze	175W HID	4000K	7,230	56	120-277V	144	080083776283	PCQT436Y
CLCSLED-86-SM-UNV	Square Surface Mount	Bronze	250W HID	4000K	11,494	92	120-277V	44	080083776108	P124NMP8
CLCSLED-86-SM-UNV-7050	Square Surface Mount	Bronze	250W HID	5000K	11,279	90	120-277V	44	080083776221	PC6DN2Q7
CLCSLED-86-SM-UNV-BPC	Square Surface Mount	Bronze	250W HID	4000K	11,494	92	120-277V	44	080083776306	
CLCSLED-117-SM-UNV	Square Surface Mount	Bronze	400W HID	4000K	13,828	121	120-277V	44	080083776160	PFXC51WH
CLCSLED-117-SM-UNV-7050	Square Surface Mount	Bronze	400W HID	5000K	13,882	120	120-277V	44	080083776245	P3J2CPH2
CLCSLED-117-SM-UNV-BPC	Square Surface Mount, PC	Bronze	400W HID	4000K	13,828	121	120-277V	44	080083776320	PCQT436Y
CLCSPEND	6" Long Pendant, 3/4"							16	080083776344	

# Caretaker LED Area/Site

Lumark

The Caretaker™ LED area luminaire delivers unmatched light output and functionality in a rugged design to address low-cost, low-maintenance security lighting applications. The versatile universal mounting plate allows quick and easy installation whether it for wall mounted security lighting, residential street lighting, perimeter area lighting, parking areas, loading platforms, boat docks, access drives or pathways. The Caretaker delivers a wide, uniform distribution with excellent vertical illumination for maximum light coverage.



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
CTKR1B	Area site with PC, UNV Mount Arm	Raw	150W HID	4000K	4,515	29	120-277V	54	080083865390	P3P0FHML
CTKR2B	Area site with PC, UNV Mount Arm	Raw	175W HID	4000K	7,110	50	120-277V	54	080083865406	PREMIUM
CTKR3B	Area site with PC, UNV Mount Arm	Raw	250W HID	4000K	9,741	71	120-277V	54	080083865413	P9E35CQB
SR-CARETAKER	Small Acrylic Refractor							240	080083699087	

# Night Falcon Floodlight

Lumark

The Night Falcon™ LED floodlight luminaire combines high-efficiency optics, superior thermal management and energy efficiency in a cost effective solution. The compact, robust design incorporates a separate driver compartment for maximum heat dissipation resulting in longer fixture and LED life. The Night Falcon luminaire uses precision engineered optics delivering superior uniformity and excellent illumination to the targeted application. Typical applications include area lighting for security, building facade lighting, accent and signage lighting in both commercial and industrial applications.



NFFLD-S



NFFLD



NFFLD-L



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
NFFLD-S-C70-KNC-UNV	Small, 6x6, Knuckle	Carbon Bronze	70W HID	4000K	2,682	20	120-277V	48	080083760282	PQEGD9D8
NFFLD-S-C70-T-UNV	Small, 6x6, Trunnion	Carbon Bronze	70W HID	4000K	2,682	20	120-277V	48	080083760299	PQEGD9D8
NFFLD-S-C15-KNC-UNV	Small, 6x6, Knuckle	Carbon Bronze	150W HID	4000K	5,797	51	120-277V	27	080083760268	P07DFEU0
NFFLD-S-C15-T-UNV	Small, 6x6, Trunnion	Carbon Bronze	150W HID	4000K	5,797	51	120-277V	36	080083760275	P07DFEU0
NFFLD-C25-S	Medium, 6x6, Slipfitter	Carbon Bronze	250W HID	4000K	10,530	85	120-277V	20	080083801244	PFT7DB3V
NFFLD-C25-T	Medium, 6x6, Trunnion	Carbon Bronze	250W HID	4000K	10,530	85	120-277V	20	080083801220	P1KJCS5UE
NFFLD-C40-S	Medium, 6x6, Slipfitter	Carbon Bronze	400W HID	4000K	16,932	128	120-277V	20	080083801206	P6WY96JR
NFFLD-C40-T	Medium, 6x6, Trunnion	Carbon Bronze	400W HID	4000K	16,932	128	120-277V	24	080083801183	P1FRZ85N
NFFLD-L-C100-S	Large, 6x6, Slipfitter	Carbon Bronze	1,000W HID	4000K	33,941	252	120-277V	6	080083800889	PXL241RW
NFFLD-L-C100-T	Large, 6x6, Trunnion	Carbon Bronze	1,000W HID	4000K	33,941	252	120-277V	6	080083800902	PWOBVSIR

# Tracer LED Floodlight

Lumark

Combining value and performance in a unique, patent-pending durable design, the Tracer LED floodlight luminaire delivers superior uniformity and excellent illumination to the targeted application. The rugged, die-cast housing is IP66 rated for exceptional durability and long term reliability. The Tracer floodlight provides design flexibility for applications such as landscape, accent, facade, or sign lighting.



TCRL



TCRS



Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
TCRS5S	Tracer Small, Spot Distribution	Carbon Bronze	50W Halogen	4000K	530	5	120-277V	360	080083884438	POR3KKF8
TCRS5M	Tracer Small, Medium Distribution	Carbon Bronze	50W Halogen	4000K	552	5	120-277V	360	080083884834	P8738XR6
TCRS5W	Tracer Small, Large Distribution	Carbon Bronze	50W Halogen	4000K	561	5	120-277V	360	080083884933	P00L69ZA
TCRS8S	Tracer Small, Spot Distribution	Carbon Bronze	70W Halogen	4000K	812	8	120-277V	360	080083884452	PCGJ8VE3
TCRS8M	Tracer Small, Medium Distribution	Carbon Bronze	70W Halogen	4000K	846	8	120-277V	360	080083884858	PM968VJ7
TCRS8W	Tracer Small, Large Distribution	Carbon Bronze	70W Halogen	4000K	860	8	120-277V	360	080083884957	P7RUSYQ7
TCRL15S	Tracer Large, Spot Distribution	Carbon Bronze	100W Halogen	4000K	1500	12	120-277V	144	080083884773	PVE80ZE4
TCRL15M	Tracer Large, Medium Distribution	Carbon Bronze	100W Halogen	4000K	1630	12	120-277V	144	080083884872	PRMSPIFM
TCRL15W	Tracer Large, Large Distribution	Carbon Bronze	100W Halogen	4000K	1657	12	120-277V	144	080083884971	PMH8U2WR
TCRL20S	Tracer Large, Spot Distribution	Carbon Bronze	120W Halogen	4000K	2039	18	120-277V	144	080083884797	PGV1B8AZ
TCRL20M	Tracer Large, Medium Distribution	Carbon Bronze	120W Halogen	4000K	2215	18	120-277V	144	080083884896	PD93F1ZM
TCRL20W	Tracer Large, Large Distribution	Carbon Bronze	120W Halogen	4000K	2251	18	120-277V	144	080083884995	PRCT0M6W
TCRL26S	Tracer Large, Spot Distribution	Carbon Bronze	150W Halogen	4000K	2718	25	120-277V	144	080083884810	PLS7UZI3
TCRL26M	Tracer Large, Medium Distribution	Carbon Bronze	150W Halogen	4000K	2953	25	120-277V	144	080083884919	PRXQGD07
TCRL26W	Tracer Large, Large Distribution	Carbon Bronze	150W Halogen	4000K	3002	25	120-277V	144	080083885015	PLDE7S49

# PRV Prevail LED Area/Site

## Lumark

The Prevail™ LED area/site luminaire delivers a new level of performance, versatility and value in a low-profile, patent-pending, architectural design that delivers significant installation and energy savings. A versatile mount arm makes retrofit installation simple, resulting in reduced installation time and additional labor savings. Ideal for general area lighting applications such as parking lots, walkways, roadways and building areas.



Outdoor

Commercial & Industrial

Catalog Number	Product Description	Finish	Replaces Up To	CCT	Lumens	Watts	Voltage	Pallet Quantity	UPC	DLC Product ID
PRVS-C15-UNV-T3	T3 Distr., STD Arm Mount	Bronze	150W HID	4000K	6,192	57	120-277V	16	080083746217	DLC Pending
PRVS-C15-UNV-T4	T4 Distr., STD Arm Mount	Bronze	150W HID	4000K	6,173	57	120-277V	16	080083753499	DLC Pending
PRVS-C15-UNV-T3-MSP/DIM-L30	T3 Distr., STD Arm Mount, Integrated Dimming Sensor	Bronze	150W HID	4000K	6,192	57	120-277V	16	080083745715	DLC Pending
PRVS-C25-UNV-T3	T3 Distr., STD Arm Mount	Bronze	250W HID	4000K	10,292	87	120-277V	16	080083746224	DLC Pending
PRVS-C25-UNV-T4	T4 Distr., STD Arm Mount	Bronze	250W HID	4000K	10,261	87	120-277V	16	080083753482	DLC Pending
PRVS-C25-UNV-T3-MSP/DIM-L30	T3 Distr., STD Arm Mount, Integrated Dimming Sensor	Bronze	250W HID	4000K	10,292	87	120-277V	16	080083745722	DLC Pending
PRVS-C40-UNV-T3	T3 Distr., STD Arm Mount	Bronze	400W HID	4000K	15,203	143	120-277V	16	080083746231	DLC Pending
PRVS-C40-UNV-T4	T4 Distr., STD Arm Mount	Bronze	400W HID	4000K	15,157	143	120-277V	16	080083753475	DLC Pending
PRVS-C40-UNV-T3-MSP/DIM-L30	T3 Distr., STD Arm Mount, Integrated Dimming Sensor	Bronze	400W HID	4000K	15,203	143	120-277V	16	080083745739	DLC Pending
PRVS-C60-UNV-T3	T3 Distr., STD Arm Mount	Bronze	450W HID	4000K	18,992	163	120-277V	16	080083773695	DLC Pending
PRVS-C60-UNV-T4	T4 Distr., STD Arm Mount	Bronze	450W HID	4000K	18,935	163	120-277V	16	080083773701	DLC Pending
PRVS-C60-UNV-T3-MSP/DIM-L30	T3 Distr., STD Arm Mount, Integrated Dimming Sensor	Bronze	450W HID	4000K	18,992	163	120-277V	16	080083773732	DLC Pending
PRVS-C60-UNV-T4-MSP/DIM-L30	T4 Distr., STD Arm Mount, Integrated Dimming Sensor	Bronze	450W HID	4000K	18,935	163	120-277V	16	080083788163	DLC Pending
PRVS-XL-C75-UNV-T3	T3 Distr., STD Arm Mount	Bronze	750W HID	4000K	26120	176	120-277V	8	080083906499	DLC Pending
PRVS-XL-C75-UNV-T4	T4 Distr., STD Arm Mount	Bronze	750W HID	4000K	26098	176	120-277V	8	080083906512	DLC Pending
PRVS-XL-C100-UNV-T3	T3 Distr., STD Arm Mount	Bronze	1,000W HID	4000K	31061	217	120-277V	8	080083906536	DLC Pending
PRVS-XL-C100-UNV-T4	T4 Distr., STD Arm Mount	Bronze	1,000W HID	4000K	31035	217	120-277V	8	080083906550	DLC Pending
PRVS-XL-C125-UNV-T3	T3 Distr., STD Arm Mount	Bronze	1,200W HID	4000K	36305	264	120-277V	8	080083906574	DLC Pending
PRVS-XL-C125-UNV-T4	T4 Distr., STD Arm Mount	Bronze	1,200W HID	4000K	36274	264	120-277V	8	080083906598	DLC Pending
PRVS-XL-C150-UNV-T3	T3 Distr., STD Arm Mount	Bronze	1,500W HID	4000K	41124	285	120-277V	8	080083906611	DLC Pending
PRVS-XL-C150-UNV-T4	T4 Distr., STD Arm Mount	Bronze	1,500W HID	4000K	41089	285	120-277V	8	80083906635	DLC Pending
PRVS-XL-C175-UNV-T3	T3 Distr., STD Arm Mount	Bronze	1,500W HID	4000K	48610	346	120-277V	8	80083906659	DLC Pending
PRVS-XL-C175-UNV-T4	T4 Distr., STD Arm Mount	Bronze	1,500W HID	4000K	48569	346	120-277V	8	080083906673	DLC Pending