ALLIED MOULDED PRODUCTS, Inc.
222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269
Email: sales@alliedmoulded.com
www.alliedmoulded.com

4304-NK



VIDEO

Product Description

Four gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 4304-NK

Height: 3-3/4 in.
Width: 7-1/2 in.
Depth: 3-9/16 in.
Volume: 75 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 4

Carton Quantity: 18
Carton Weight: 20 lb.

UPC: 085339175513
UNSPSC: 39121308
Country of Origin: United States of America

FEATURES

Machine tapped device holes, slot provision for low voltage divider, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

APPLICATION

New work residential construction 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594

UL LISTED

FIRE CLASSIFICATION

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Polyvinyl chloride clamps

© 2017 Allied Moulded Products, Inc.