

D.

DEFINITIVE TECHNOLOGY



Mythos Three-Channel Passive Sound Bar

The Mythos® Series three-channel sound bars elevate home theater experiences indoors and out. Combining the three front channels of a home theater system in a single cabinet, these ultra-slim, on-wall speakers blend high-performance sound and designer aesthetics in a weather-protected, adjustable-width rigid aluminum enclosure. Mythos Series three-channel sound bars are available in three models.

KEY BENEFITS

Slim Profile with Luxury Finishes

Ultra-slim, wall-mount cabinet measures less than 2" deep and features clean, modern aesthetics; and refined anodized aluminum finishes. Symmetrically adjustable extensions expand from 3.5" (on 3C-65 and 3C-75) to 6.75" (on the 3C-85) to perfectly match the width of 65", 75", or 85"-class displays for a sleek, streamlined appearance under your TV.

Acoustically Optimized Cabinet

A highly rigid, tuned aircraft-grade aluminum enclosure houses the speaker array, with each channel in its own acoustic chamber. You'll experience the truest sound, uncolored by cabinet resonances.

IP66-Rated Weather Protection

Water- and dust-resistant construction means you can enjoy stunning home theater sound outdoors.

Multi-Driver Arrays

Mythos three-channel passive sound bars feature two- and three-way driver arrays. Multiple-driver arrays improve driver performance and project robust, full-range sound over a wide area.

XTDD Drivers

Ultra-stiff, 3.5", anodized aluminum dome woofers and midrange drivers eliminate breakup and broaden dispersion, for crisp, clear sound and a spacious, enveloping soundstage.

Aluminum Oxide Dome Tweeters


Rigid, 1", well-damped Dymension™ Series tweeters deliver smooth extended response, crisp transients, and pin-point imaging, for cohesive, lifelike sound that draws you inside the action.

Timbre-Matched

Consistent sound across Definitive Technology models gives you the flexibility to mix and match speakers to build the ultimate system or a starter system that can expand as your needs grow.

PRODUCT FEATURES

- On-wall, passive sound bar blends high-performance sound and designer aesthetics
- IP66-rated weather-resistant design is suitable for use outdoors
- 3.5" XTDD woofers and 3.5" XTDD midrange drivers deliver balanced lows and mids
- 1" aluminum oxide dome tweeters deliver precise highs, lifelike realism
- Precision crossovers optimize drivers for full, lifelike sound
- Included VESA and wall-mount brackets provide a seamless appearance



Mythos® Three-Channel Passive Sound Bar

SPECIFICATIONS			
	3C-65	3C-75	3C-85
Dimensions (H × D)	6.25 × 1.87 in. (159 × 48 mm)	6.25 × 1.87 in. (159 × 48 mm)	6.25 × 1.87 in. (159 × 48 mm)
Adjustable Width (W)	56.5 × 60 in. (1435 × 1524mm)	65.8 × 69.2 in. (1671 × 1758 mm)	72.8 × 79.5 in. (1849 × 2019 mm)
Symmetrically Adjustable Extensions	3.4 in. (86 mm)	3.4 in. (87 mm)	6.25 in. (159 mm)
Weight	17 lbs (7.8 kg)	20 lbs (9.3 kg)	22 lbs (10.1 kg)
Color / Material	Black anodized aluminum	Black anodized aluminum	Black anodized aluminum
Grille Material	Micro-perforated powder-coated steel	Micro-perforated powder-coated steel	Micro-perforated powder-coated steel
Tweeter	(3) 1 in. aluminum oxide dome	(3) 1 in. aluminum oxide dome	(3) 1 in. aluminum oxide dome
Midrange	-	(2) 3.5 in. XTDD aluminum dome	(2) 3.5 in. XTDD aluminum dome
Woofer	(8) 3.5 in. XTDD aluminum dome	(8) 3.5 in. XTDD aluminum dome	(8) 3.5 in. XTDD aluminum dome
Number of Channels	3 (left,center, right)	3 (left,center, right)	3 (left,center, right)
Frequency Response	100 Hz-25 kHz (-10dB) 120 Hz-20 kHz (-3dB)	100 Hz-25 kHz (-10dB) 120 Hz-20 kHz (-3dB)	100 Hz-25 kHz (-10dB) 120 Hz-20 kHz (-3dB)
Nominal Impedance	4Ω (8Ω compatible)	4Ω (8Ω compatible)	4Ω (8Ω compatible)
Sensitivity	88dB (2.83V/1m)	88dB (2.83V/1m)	88dB (2.83V/1m)
Recommended Amplifier Power	80W	80W	80W
IP Rating (Ingress Protection)	IP66	IP66	IP66
Warranty	5-year	5-year	5-year
Included Accessories	(2) VESA-mount brackets and spacers (1) Wall-mount bracket	(2) VESA-mount brackets and spacers (1) Wall-mount bracket	(2) VESA-mount brackets and spacers (1) Wall-mount bracket

