



NOTES: (UNLESS OTHERWISE SPECIFIED)

1. ALL DIMENSIONS ARE IN INCHES.
2. TOLERANCE ON ALL DIMENSIONS IS  $\pm 0.010^*$ .
3. CONTINUOUS RUN OF THREAD FROM LINER-WELL TO 'S-2' DIMENSION SHOWN AT BOTTOM OF SKIRT. (2 FULL TURNS)

# FoilSeal™ Data Sheet

## .020" Pulp FSM-1

Revision: FSM1-06042010

<b>Product</b>	.020" Pulp FSM-1		
<b>Scope</b>	Two piece pulp backed heat induction foil innerseal that will provide a tamper-evident bond to PE containers.		
<b>Composition</b>	<b>Material</b>	<b>Standard</b>	<b>Metric</b>
	Backing	.020"	.508 mm
	Wax	-	-
	Foil	.001"	.0254mm
	PET	.0005"	.0127mm
	Heat Seal	.0015"	.0381mm

Composition does not include adhesive, resin or wax bonding layers (if any).

<b>FDA Status:</b> 21 CFR 177.1210	<b>Recommended Storage and Handling:</b> Refer to website	
<b>Drug Master File (DFM):</b> #4544	<b>EU / EP Reg.:</b>	
<b>GTR Oxygen:</b> Essentially Zero	<b>MVTR:</b> Essentially Zero	
<b>Print Location (if any):</b> Foil Layer and/or Heat Seal Layer		

Materials are compliant with current USFDA Food allergen Guidelines.  
 Materials are compliant with California Proposition 65 labeling requirements.  
 Materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

DISTRIBUTED BY: 	REF NO.: DWG30492
DESCRIPTION: 63 mm PP Smooth Top, Ribbed Sides Buttress Cap, .020 Pulp FSM-1 Liner	

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.