

Cat. No.	XLF100
Notes	

Section 10309 - Manufactured Electric Fireplaces

PART 1 GENERAL

1.1 SECTION INCLUDES

- Manufactured electric fireplaces.
- B. Accessories.

1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

1.3 REFERENCES

- A. UL 2021
- B. CSA C22.2 No. 46

1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

1.6 WARRANTY

A. Provide the manufacturers 2 year limited warranty on electrical components.

PART 2 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
 - 1. Base: Dimplex Electric Fireplace

Dimplex North America

1367 Industrial Road

Cambridge ON N3H 4C3

1-888-DIMPLEX

www.dimplex.com

archdesign@dimplex.com



Cat. No.	XLF100
Notes	

Section 10309 - Manufactured Electric Fireplaces

- 2. Substitutions not permitted
- Requests for substitutions will be considered in accordance with provisions of Section 01600.

2.2 ELECTRIC FIREPLACES

- A. General:
 - 1. Provide all components and accessories required for a complete, functional unit.
 - 2. UL or CSA listed.
- B. Pre-fabricated Electric Fireplace:
 - Base Product:
 - a) Dimplex Linear Electric Fireplace
 - b) Model Number: XLF100
 - 2. Description: Realistic 100" wall-mounted linear electric fireplace
 - 3. Dimensions:
 - a) Width: 100-1/4" / 2547mmb) Height: 15-5/8" / 398mmc) Depth: 5-7/8" / 148mm
 - 4. Framing Dimensions:
 - a) Width: 100-5/8" / 2556mmb) Height: 16" / 460mm
 - c) Depth: 5-7/8" / 149mm
 - 5. Electrical:
 - a) Volts: 120 / 240
 b) Watts: 1,500 / 2,500
 c) BTUs: 5,118 / 8,530
 d) Amps: 12.5 / 10.4
 - 6. Venting: Non-venting
 - 7. Operation: Flame only, flame and heat
 - 8. Heating: Louver-less, fan-forced circulation
 - 9. Liner: Steel
 - 10. Standard features:
 - a) Flame/ember bed on/off, range of color themes
 - b) Acrylic crystal ember bed with sparkle effect
 - c) LED flame technology
 - d) Pre-set and custom color effects
 - e) On-demand ceramic heater, with heat boost and ECO-mode
 - f) Hard wire capabilities 120V, 240V
 - g) Built-in touch controls
 - h) Seamless installation and edge to edge glass
 - 11. Optional Media Bed Accessories:
 - a) Driftwood and river rock accessory package (includes one large and one small piece of driftwood, with loose rocks)



Cat. No.	XLF100				
Notes					

Section 10309 – Manufactured Electric Fireplaces

12. Control options:

- a) Multi-function remote control
- b) Built-in membrane controls (Flame on/off, heat on/off, thermostat, colour options)

PART 3 EXECUTION

3.1 INSPECTION

- Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION