HUBBELL Wiring Device-Kellems

Locking Devices, Twist-Lock®, Industrial, Male Plug, 20A 125/250V 3- Pole 4-Wire Grounding, L14-20P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems Catalog # HBL2411

Locking Devices, Twist-Lock®, Industrial, Male Insulgrip® Plug, 20A 125/250V AC, 3- Pole 4-Wire Grounding, NEMA L14-20P, Screw Terminal, Black and White Nylon.



General

Application

Catalog Number

Color

Cord Range

0.350"-1.150" (9-29)

EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

HBL2411

Horsepower - Maximum

20A Male Insulgrip® Plug Item Type

Material

Material - Mounting Hardware Cord Mounted

Number Of Poles

Maximum continuous 75°C and Operating Temperature

minimum -40°C without Impact

Performance Electrical - Current Interrupting

> - Certified for current interrupting at full rated

current

3-Pole

Electrical - Dielectric Voltage -Withstands 2,000V minimum

Environmental - Flammability -HB or better per UL94/CSA

22.2 No.0.17

Environmental - Moisture Resistance - IP20 Suitability

Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Mechanical - Terminal

Accommodation - #16 AWG -#8 AWG stranded copper wire

only.

Mechanical - Terminal **Identification - Terminals** identified in accordance with

UL 495

Type Plugs

Plugs

UPC 783585038131

Dimensions

Dimensions 2.33 in x 2.33 in x 2.75 in

Standard Sized Display Size

2.75 in Height Length 2.33 in Weight 0.2 lbWidth 2.33 in

Electrical Ratings

20 A Amperage Rating

Connectivity Pressure Terminal Screws

Current / Amperage Rating 20 A Current Rating 20 A

Dielectric Strength Withstands 2,000V minimum

Phase Single Phase Voltage Rating 125/250 VAC Voltage Rating Description 125/250 VAC

Conductor Related

Cable Range 0.350 - 1.150 in Cord Type All Listed Portables

Number Of Wires 4-Wire

#16 AWG to #8 AWG Wire Size

Certifications And Compliance

Industry Standard(s) Certified to CSA C22.2 No.42

Fed.Spec. W-C-596

Listed to UL 498

Nema Rating L14-20P Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 30 Pallet Quantity 3060

Product Assets

Catalogs - WDK Catalog Full 2024

Warranty - Industrial & Commercial Products



©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL2411-SPEC-EN | REV 6/2024