

Non-shielded Plenum Control Cable - 16 AWG & 18 AWG

Non-shielded Plenum

Security and Alarm Cable



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper

Category Insulation Description:

- Premium-grade Polyvinyl Chloride (PVC)

Category Jacket Description:

- Premium-grade Polyvinyl Chloride (PVC)

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725-CL3P, CMP, MPP

PART NUMBER TABLE						
Part#	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
G121802	18	2	.008"	.015"	.156"	16
G121803	18	3	.008"	.015"	.166"	23
G121804	18	4	.008"	.015"	.187"	30
G121805	18	5	.008"	.015"	.200"	36
G121806	18	6	.008"	.015"	.216"	43
G121808	18	8	.008"	.015"	.235"	58.2
G121810	18	10	.008"	.015"	.268"	70.6
G121812	18	12	.008"	.015"	.278"	83.2
G121602	16	2	.008"	.015"	.174"	21
G121603	16	3	.008"	.015"	.185"	21
G121604	16	4	.008"	.015"	.205"	38

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
 Seattle • St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC