

Tempo



Colors



White
VTL TPWH




Tan
VTL TPTN




Taupe
VTL TPTP



Brown
VTL TPBR



Light Gray
VTL TPLG



Medium Gray
VTL TPMG



Black
VTL TPBK



Forest Green
VTL TPGF



Green
VTL TPGN




Orange
VTL TPOR



Red
VTL TPRD



Blue Gray
VTL TPBG



Sky Blue
VTL TPSB



Navy
VTL TPNV

Sizes




2" Hexagon Mosaic




Oval Mosaic




Chevron Mosaic



2" Circle Mosaic



Lento Mosaic



Presto Mosaic

TEMPO

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
2" x 2" Presto Mosaic	11.63" x 12.00"	6.00mm	Matte/Natural
2" x 2" Hexagon Mosaic	11.75" x 12.00"	6.00mm	Matte/Natural
2" x 2" Circle Mosaic	11.38" x 11.50"	6.00mm	Matte/Natural
1" x 4" Oval Mosaic	11.75" x 12.50"	6.00mm	Matte/Natural
0.625" x 2" Chevron Mosaic	11.63" x 12.00"	6.00mm	Matte/Natural
0.625" x 2" Lento Mosaic	11.63" x 12.00"	6.00mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Recommended Grout Joint: 1/8" - Rectified
3/16" - Non Rectified



Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	523 lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Class A
DCOF	≥0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	0
Certifications	N/A
Country of Origin	N/A
Shade Variation Code	V3

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glass



Stock and Import



V3 Moderate Variation



DCOF: ≥0.42



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com



VITL
COMMERCIAL SURFACES