

F1960 Brass PEX Ball Valve

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

- Lead-free brass
- 5 year limited warranty
- Working pressure: 80 psi
- Max. pressure: 200 psi
- Working temperature: 73°F
- Max. temperature: 200°F
- Temperature and pressure ratings: 200 psi at 200°F
- Dezincification-Resistant (DZR)



Applications

- PEX Pipe

Materials

- Brass body
- Steel handle

Dimensions and Product Offering

Part Code	Size	A	B	C	D	E
B65050LF	1/2"	2.53" ±0.1"	1.64 ± 0.25"	3.78 ± 0.25"	Ø 0.38"	Ø 0.61"
B65075LF	3/4"	3.29" ±0.1"	1.88" ± 0.25"	3.78 ± 0.25"	Ø 0.60"	Ø 0.87"
B65100LF	1"	3.94" ±0.1"	2.01" ± 0.25"	3.78 ± 0.25"	Ø 0.80"	Ø 1.10"
B65125LF	1-1/4"	5.01" ±0.1"	2.58" ± 0.25"	4.37 ± 0.25"	Ø 0.96"	Ø 1.35"
B65150LF	1-1/2"	5.54" ±0.1"	2.64" ± 0.25"	4.37 ± 0.25"	Ø 1.08"	Ø 1.49"
B65200LF	2"	7.21±0.1"	3.10" ± 0.25"	6.24 ± 0.25"	Ø 1.55"	Ø 2.07"

Certifications/Listings/Approvals

- Vermont Act 193 compliant
- Lead Law compliant
- IAPMO/ANSI Z1157
- ASME A112.4.14/CSA B125.14
- NSF/ANSI 14
- NSF/ANSI/CAN 372
- NSF/ANSI/CAN 61

