

SAVANT PRO AUDIO 4

Press Play on A Scalable, All-In-One Audio Solution



SAVANT

savant.com

©2016 Savant Systems, LLC. All rights reserved.

KEY FEATURES

THE TOTAL AUDIO PACKAGE

A true all-in-one experience, the Pro Audio 4 features built-in streaming, distribution, and amplification for complete audio immersion.

MUSIC IN EVERY ROOM

The Pro Audio 4 provides four zones of high-quality audio that syncs automatically between rooms, so you never miss a note. Play it all, straight from the Savant Pro App or your Pro Remote.

STREAM FREELY

The Pro Audio 4 includes a single stream of Savant Music, with support for an additional stream through the Savant Smart Host, so you can personalize the music in any room.

EXPAND YOUR REACH

Connect up to three Pro Audio 4 units to get twelve distinct audio zones and three Savant Music streams, and add even more rooms to your musical range.

AUDIOPHILE APPROVED

Your music comes in with perfect clarity. The high-quality 50 watt amplifier, with integrated audio processing, gives you four stereo zones of unmatched, immersive fidelity.

EASY INSTALLATION

With rack, structured media, and credenza mounting options, the Pro Audio 4 can adapt to most spaces, making it simple to install anywhere.

SPECIFICATIONS

ENVIRONMENTAL

Temperature 32° to 104° F (0° to 40° C)

Humidity 10% to 80% (non-condensing)

Maximum BTU 750 BTU/HR

POWER

Input Power 100/240V AC (50/60 Hz) 2.7A

Maximum Power 225W

COMPLIANCE

Safety and Emissions FCC Part 15B | CE Mark | UL | C-Tick

RoHS Compliant

MINIMUM SUPPORTED RELEASE

Savant OS: da Vinci 8.2

Requires pairing with a Savant Smart Host or Pro Host

CONTROL PORTS

4 IR ports

2 RS-232 ports

DIMENSIONS

Height 3.03 in (7.7 cm)

Width 12 in (30.5 cm)

Depth 14.17 in (36.0 cm)

Weight 10.6 lb (4.81 kg)

Rack Space 2U

OPERATING PARAMETERS

Rated Power (Speaker Output) 50 WPC at 8 ohms (THD+N < 0.1%)
70 WPC at 8 ohms (THD+N < 1.0%)

Frequency Response 20 Hz - 20 kHz +/- 0.5 dB, speaker output

Signal-to-Noise Ratio (SNR) >95 dB, speaker output

Supported Digital Input Formats 44.1 kHz / 48 kHz / 96 kHz at 16-bit / 20-bit / 24-bit resolution

SCALABILITY

Connect up to 3 units using AVB compliant switching

Enable 18 zones of distributed audio (12 amplified, 6 pre-amp)

Includes 2 additional line level output zones

SAVANT

savant.com