Kavala

Colors

Satyr | VTL KASA

Pegasus | VTL KAPE

Nemean | VTL KANE

Minotaur | VTL KAMI

Gorgon | VTL KAGO

Sizes



12" x 24" x 8mm

KAVALA

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
12” x 24”	11.81” x 23.62”	8.00mm	Matte/Natural

* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
2” x 2” Mosaic	12.00” x 12.00”	Matte/Natural
3” x 12” Bullnose	3.00” x 12.00”	Matte/Natural
6” x 12” Cove Base	6.00” x 12.00”	Matte/Natural

Recommended Grout Joint: 1/8” - Rectified
3/16” - Non Rectified

Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 300lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	≥ 7
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.5%
Certifications	Greenguard Bureau Veritas NSF EPD
Country of Origin	USA
Shade Variation Code	v2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Material

Color-Body Porcelain

Made in USA

Ready Ship

V2 Slight Variation

DCOF: ≥ 0.42

Greenguard, Bureau Veritas
NSF EPD

Scan QR Code for Product Information and Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

VITL SURFACES COMMERCIAL