



Technical Specifications: Aimpoint 5000/
5000 Mag Dot*

You have chosen an Aimpoint® red-dot sight, an advanced sight for the demanding sport of shooting. Aimpoint red-dot sights are developed from the demands of hunters and competitive shooters worldwide. Rough construction, parallax-free optics, state-of-the-art electronics and low weight makes the Aimpoint red-dot sights the natural choice for every quality minded shooter.

MOUNTING:

The Aimpoint red-dot sight is basically to be mounted with the two enclosed 30 mm rings (two 25 mm rings for the Aimpoint 3000). To ensure repeatability and optimal adjustment area, be sure to follow the instructions for each mount properly. Before it is tightened, you will be able to rotate the sight in the rings so that the electronic device can be placed on which side you want ①.

WINDAGE AND ELEVATION ADJUSTMENT:

The sight has a circular sized adjustment area, with a diameter of 8.5 ft. at 100 yds. To adjust, unscrew the protection caps from the adjustment screws ③. The screws are equipped with a slot that fits a coin. Turn the adjustment screws until you reach the point of impact you prefer. When moving the point of impact to the right, screw the windage adjustment screw counterclockwise (for leftside mounting clockwise). When moving the point of impact to the left, screw the windage adjustment screw clockwise (for leftside mounting counterclockwise). When moving the point of impact upwards, screw the elevation adjustment screw counterclockwise (for leftside mounting also counterclockwise). When moving the point of impact downwards, screw the windage adjustment screw clockwise (for leftside mounting also clockwise). Each click of the adjustment screw makes a 1/2 in. movement of the point of impact at 100 yds. The adjustment is centered when the sight leaves the factory, to provide maximum adjustment possibilities in every direction. Therefore do not adjust screws until the sight is mounted on your firearm.

LIGHT ADJUSTMENT AND BATTERIES:

The sight is equipped with a rotary switch with ten positions ④. One OFF-position and nine positions for different dot intensity settings. The sight comes equipped with one lithium battery DL 1/3 N ⑤. In cold weather situations we recommend lithium or silveroxide batteries, which have better low temperature characteristics. Zinc-oxygen batteries are not recommended. Due to the need of oxygen to work. The sight is packed with fresh batteries from the factory.

Aimpoint, Inc. reserves the right to change or improve our products as we find necessary. This manual describes the product at the time of this publication.

Aimpoint
For USA and Canada:
580 Herndon Parkway
Suite 500,
Herndon, VA 22070, USA
Phone (703) 471-6828
Fax (703) 689-0575

For all other countries:
Jägershillgatan 15
S-213 75 Malmö, Sweden
Phone +46 (0) 40 21 03 90
Fax +46 (0) 40 21 92 38

System:	100% parallax free
Optics:	Anti-reflex coated lenses
Eye relief:	Unlimited
Batteries:	2 x Mercury SP 675 1 x Lithium 2L76 or DL1/3N
Battery life:	250-500 hours
Adjustment:	1 click = 1/4" at 100 yds.
Length:	5.5" (146 mm)
Weight:	5.8 oz (172 gr)
Objective dia:	36 mm
Dot dia:	3" at 100 yds. (3 MOA) *3" at 30 yds. (10 MOA)
Mounting system:	30 mm rings
Magnification:	1X
Material:	Anodized aluminium, stainless or black finish.