

# MODERN FORMATION™



## COLORBODY™ PORCELAIN STONEWARE

TRUEEDGE™ | REVEAL IMAGING™ | STEPWISE™\*

### FLOOR TILE - AVAILABLE IN LIGHT POLISHED, UNPOLISHED & TEXTURED\*



**MF01** Peak White



**MF02** Overland Beige



**MF03** Canyon Taupe



**MF04** Headland Fog



**MF05** Smoky Ridge



**MF06** Mesa Point

### MIXED CHEVRON MOSAIC\*\*

12 x 12 SHEET



**MF01** Peak White



**MF02** Overland Beige



**MF03** Canyon Taupe



**MF04** Headland Fog



**MF05** Smoky Ridge



**MF06** Mesa Point

### 2 x 2 MOSAIC - UNPOLISHED

12 x 12 SHEET



**MF01** Peak White

**MF01** Peak White  
**MF02** Overland Beige  
**MF03** Canyon Taupe  
**MF04** Headland Fog  
**MF05** Smoky Ridge  
**MF06** Mesa Point

### 12 x 24 - TEXTURED WITH STEPWISE™ TECHNOLOGY\*



**MF01** Peak White

**MF01** Peak White  
**MF02** Overland Beige  
**MF03** Canyon Taupe  
**MF04** Headland Fog  
**MF05** Smoky Ridge  
**MF06** Mesa Point

### USAGE

Floors	Walls	Countertops
F	W	C

\*StepWise™ available in 12 x 24 Textured finish only

\*\*Mixed Chevron Mosaic is a mix of Light Polished, Unpolished, & Textured finishes

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	(23-7/16" x 46-7/8") (59.44 cm x 119.30 cm)	3/8"	15.26	2
	24 x 24 Floor Tile	(23-7/16" x 23-7/16") (59.44 cm x 59.44 cm)	3/8"	15.2	4
	12 x 24† Floor Tile	(11-11/16" x 23-7/16") (29.56 cm x 59.44 cm)	3/8"	15.12	8
	2 x 2 Mosaic - Unpolished (Mesh-mounted)	(12" x 12") (30.48 cm x 30.48 cm)	3/8"	10	10
	Mixed Chevron Mosaic* (Mesh-mounted)	(12" x 13") (30.48 cm x 33.02 cm)	3/8"	9.3	10

†Also available in Textured finish with StepWise™ technology

\*Available in a mix of Light Polished, Unpolished & Textured finishes

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■◊
Shower Floors (Residential or Light Commercial)	≥ 0.42	■▲
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	■◊
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■▲

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

◊Unpolished and Textured only

▲2 x 2 Mosaics only

\*12 x 24 Textured with StepWise™ only



All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).

## TRIM

Description	Number	Size	Shape
Floor Bullnose	P-43F9	3 x 24*	
Cove Base	P-36C9T	6 x 12	
Cove Base Outcorner	PC-36C9T	1 x 6	

\*Available in Unpolished and Light Polished

Floor bullnose, cove base, and cove base outcorner trim are intended to coordinate with floor tile in the standard 90-degree installation position.

Cove base and cove base outcorner are suitable for non-freezing climates only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 High (V3)

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmations should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

\*StepWise™ available in 12 x 24 Textured finish only