

Beldray^{est 1872}®

Our **portable,**
practical &
convenient
halogen
heater



1200 W
HALOGEN
HEATER
INSTRUCTION MANUAL

* This product is only suitable for well-insulated spaces or occasional use.



www.beldray.com

Please retain instructions for future reference.

WARNING - READ BEFORE USE

Do not leave the product unattended while in use.

This product can be used for no longer than 4 hours, after which time it must be switched off and allowed to cool fully before it is used again.

The product must be used on a stable, heat-resistant surface.

The product must be placed at least 1 metre away in every direction from walls, doors, furniture, curtains, or any other flammable materials.

Read all of the instructions carefully before replacing the halogen heating tubes. If unsure, consult a qualified electrician.

Safety Instructions

When using electrical products, basic safety precautions should always be followed.

Check that the voltage indicated on the rating plate corresponds with that of the local network before connecting the product to the mains power supply.

Children younger than 3 years old should be kept away from the product unless continuously supervised.

Children aged from 3 years and less than 8 years should not plug in, regulate or clean the product or perform user maintenance.

Children aged from 8 years and people with reduced physical, sensory or mental capabilities or lack of experience and knowledge can use this product, only if it has been placed in its intended operating position and they have been given supervision or instruction concerning use of the product in a safe way and understand the hazards involved.

Children should not perform cleaning or user maintenance unless they are older than 8 years and supervised.

This is not a toy – children should be supervised to ensure they do not play with the product.

Always unplug the product and allow to cool fully after use and before any cleaning or maintenance.

Normal voltage is still present in this product as long as the product is connected to the electrical source.

This product contains no user serviceable parts. If the power supply cord, plug or any part of the product is malfunctioning or if it has been dropped or damaged, only a qualified electrician should carry out repairs. Improper repairs may place the user at risk of harm.

Keep the product and its power supply cord out of the reach of children and away from heat or sharp edges that could cause damage. This includes any parts of the product that may become hot during use and other heat emitting products.

Keep furniture, curtains and other flammable material at least 1 metre away from the product.

Do not run the supply cord under carpets, rugs etc. or anywhere where it may present a trip hazard.

Do not immerse the product or plug in water or any other liquid.

Do not operate the product with wet hands.

Do not use this product in the immediate surroundings of a bath, a shower or swimming pool.

Do not leave the product unattended whilst connected to the mains power supply or when in use.

Do not remove from the mains power supply by pulling the cord; switch off and remove the plug by hand.

Do not use this product for extended periods of time.

Do not leave the product plugged in or operating overnight.

Do not use the product for anything other than its intended use.

Do not block the air vents of the product; place in an open, well-ventilated space.

Do not use this product outdoors.

Do not attempt to move the product whilst it is in use.

Do not put objects into any of the openings.

Do not use the product with a programmer, timer, separate remote-control system or any other device that will switch the product on automatically, as there is a risk of fire if the heater is covered or positioned incorrectly.

Do not clean the product with abrasive chemicals or materials such as scourers as they may damage the product and impair future function. This includes insecticide and chemical solvents.

Only lift the product with the carry handles provided.

The product should be used on a stable, heat-resistant surface.

The product must not be located immediately below or next to a mains power supply.

Never use accessories that are not recommended or supplied by the manufacturer. It could cause danger to the user and damage to the product.

Use of an extension cord with the product is not recommended. This product is intended for domestic use only. It should not be used for commercial purposes.

Caution: Some parts of this product can become very hot and cause burns. Particular attention has to be given where children and vulnerable people are present.



Hot surface – do not touch the hot section or heating components of the product.



Warning: In order to avoid overheating, do not cover the product.

This product is not equipped with a device to control the room's temperature.

Do not use this product in small rooms whilst occupied by persons incapable of leaving the room on their own, unless constant supervision is provided.

Stability Safety Cut-out

This halogen heater is fitted with a stability safety cut-out. This will automatically switch off the halogen heater if it is not in the upright position. Once the halogen heater has been correctly placed in an upright position, it will resume normal operation.

Thermal Cut-out Device

The halogen heater is fitted with a thermal safety cut-out device, built in to prevent it from overheating. Should the halogen heater start to overheat, the thermal safety cut-out system will automatically operate and the heat settings will switch off. If this happens:

STEP 1: Switch off the halogen heater using the activated heat setting switch.

STEP 2: Check that the halogen heater is unplugged from the mains power supply and allow it to cool for approx. 15 minutes.

STEP 3: Clear any blockages present on the vent, being careful not to damage the halogen heater.

STEP 4: Plug in and switch on the halogen heater at the mains power supply.

Caution: In order to avoid a hazard, due to inadvertent resetting of the thermal cut-out, this halogen heater must not be supplied through an external switching device such as a timer or connected to a circuit that is regularly switched on and off by the utility.

Care and Maintenance



Always unplug the halogen heater from the mains power supply and allow to cool sufficiently before performing any cleaning or maintenance.

Wipe the halogen heater with a soft, damp cloth and allow to dry thoroughly.

Do not use harsh or abrasive cleaning solvents, as these may damage the finish of the halogen heater.

Do not immerse the halogen heater in water or any other liquid.

Description of Parts



- | | |
|-------------------------------------|---|
| 1. 1200 W Halogen Heater main body | 8. Reflector (behind halogen heating tubes) |
| 2. Carry handle | 9. Lattice mesh guard |
| 3. Oscillation switch | 10. Base stand |
| 4. Power switch 1 (for bottom tube) | 11. Cord clips |
| 5. Power switch 2 (for middle tube) | 12. Removable side panels (each side) |
| 6. Power switch 3 (for top tube) | |
| 7. Halogen heating tubes | |

Instructions for Use

Before First Use

STEP 1: Check that there is no damage to the halogen heater.

STEP 2: Remove the white-capped screws from the bottom of the halogen heater main body using a flat head screwdriver and put them to one side.

STEP 3: Feed the power supply cord through the cord clips on the bottom of the base stand; this will keep the power supply cord fixed into position.

STEP 4: Fix the base stand onto the halogen heater using the white-capped screws.

STEP 5: Position the halogen heater on a flat, stable, heat-resistant surface in an open space, at least 1 metre away from furniture, curtains or any other flammable materials.

Note: When using the halogen heater for the first time, a slight odour may be emitted. This is normal and will soon subside. Allow for sufficient ventilation around the halogen heater.

Caution: The halogen heater will only fit one way onto the base stand; do not attempt to force it.

Replacing the Halogen Tubes

Switch off and unplug the halogen heater from the mains power supply before attempting to replace the halogen tubes.

It is recommended to have replacement bulbs fitted by a qualified electrician, to avoid damage or injury.

STEP 1: Remove each side panel by unfastening the top and bottom screws.

STEP 2: Slide back the plastic cover on the clip of the halogen tube that needs to be replaced. Detach the clip from the halogen tube by gently pressing the locking mechanism and pulling the clip away. Repeat for each side of the halogen tube.

STEP 3: Gently bend the metal tabs and remove the mica panel from each side of the halogen tube that needs to be replaced.

STEP 4: Taking hold of one side of the halogen tube by the plastic end, carefully remove it from the halogen heater. Check that the halogen heater has cooled down sufficiently before attempting to replace halogen tubes. Take care not to drop the halogen tube inside the halogen heater whilst removing.

STEP 5: Holding the plastic ends of the replacement halogen tube, carefully insert it into the halogen heater. Do not touch the glass casing as this can reduce the lifespan of the halogen tube. Replace the mica panels over each end of the halogen tube and then secure the metal tabs back into position. Reattach the clip and then slide the plastic cover over the clip for protection. Check that the clip has locked properly by gently pulling on the connection.

STEP 6: Fasten each side panel back onto the halogen heater.

Note: To purchase replacement halogen tubes, visit www.no1brands4you.com.

Using the 1200 W Halogen Heater

STEP 1: Plug in and switch on the halogen heater at the mains power supply.

STEP 2: To turn on the halogen heater, select the desired heat output by pressing power switch 1, 2 or 3 to the 'I' position.

To operate the halogen heater on a low heat setting (400 W), press one of the switches. To operate the halogen heater on a medium heat setting (800 W), press any two of the power switches to the 'I' position.

Press all three of the power switches to the 'I' position to operate the halogen heater on the highest heat setting (1200 W).

STEP 3: Activate the oscillation function by pressing the oscillation switch to the 'I' position; the halogen heater will begin to turn left and right. To stop the halogen heater from turning, press the oscillation switch to the '0' position.

STEP 4: Should the position of the halogen heater need to be changed, switch off and unplug it from the mains power supply. Once cooled, move the halogen heater using the carry handle at the rear, checking that there is sufficient cable length available before moving.

STEP 5: Turn off the halogen heater by pressing any active power switches to the '0' position.

Caution: Check the halogen heater for damage before each use. Do not use if damaged.
Do not use the product for extended periods of time.

Troubleshooting

Problem	Cause	Solution
The halogen heater does not heat up.	The power switches have not been selected.	Switch on one, two or three of the power switches, as indicated in the section entitled 'Using the Halogen Heater'.
The halogen heater does not function.	The stability cut-out has activated.	The stability cut-out will deactivate once the halogen heater has been put back in the upright position.
	The fuse has blown.	Unplug the halogen heater from the mains power supply and replace the fuse with one that is the same amp.

Storage

Check that the halogen heater is completely cool before storing in a cool, dry place. Never wrap the cord tightly around the halogen heater; wrap it loosely to avoid causing damage.

Specifications

Product code: EH0197SSTK
Voltage: 220–240 V ~ 50 Hz
Power: 1200 W

ERP Table

Item	Symbol	Value	Unit	Item	Unit
Heat Output				Type of heat input for electric storage local space heaters only (select one).	
Nominal heat output	P_{nom}	1.2	kW	Manual heat charge control, with integrated thermostat.	No
Nominal heat output (indicative)	P_{min}	0.4	kW	Manual heat charge control with room and/or outdoor temperature feedback.	No
Maximum continuous heat output	$P_{max,c}$	1.2	kW	Electronic heat charge control with room and/or outdoor temperature feedback.	No
Auxiliary electricity consumption				Fan assisted heat output.	No
At nominal heat output	$e_{l_{max}}$	N/A	kW	Type of heat output/room temperature control (select one).	
At minimum heat output	$e_{l_{min}}$	N/A	kW	Single stage heat output and no room temperature control.	No
In standby mode	$e_{l_{SB}}$	0	kW	Two or more manual stages, no room temperature control.	Yes
				With mechanic thermostat room temperature control.	No
				With electronic room temperature.	No
				Electronic room temperature control plus day timer.	No
				Electronic room temperature control plus week timer.	No
				Other control options (multiple selections possible).	
				Room temperature control, with presence detection.	No
				Room temperature control, with open window detection.	No
				With distance control option.	No
				With adaptive start control.	No
				With working time limitation.	No
				With black bulb sensor.	No

Connection to the mains

Please check that the voltage indicated on the product corresponds with your supply voltage.

Important

As the colours in the mains lead of this appliance may not correspond with the coloured markings identifying the terminals in your plug, please proceed as follows:


The wires in the mains lead are coloured in accordance with the following code:

Blue Neutral (N)

Brown Live (L)

Green/Yellow Earth (\perp)

FOR UK USE ONLY - Plug fitting details (where applicable).



The wire coloured BLUE is the NEUTRAL and must be connected to the terminal marked N or coloured BLACK.

The wire coloured BROWN is the LIVE wire and must be connected to the terminal marked L or coloured RED.

The wire coloured GREEN/YELLOW must be connected to the terminal marked with the letter E or marked \perp .

On no account must either the BROWN or the BLUE wire be connected to the EARTH terminal (\perp).

Always ensure that the cord grip is fastened correctly.

The plug must be fitted with a fuse of the same rating already fitted and conforming to BS 1362 and be ASTA approved.

If in doubt consult a qualified electrician who will be pleased to do this for you.

Non-rewireable mains plug

If your appliance is supplied with a non-rewireable plug fitted to the mains lead and should the fuse need replacing, you must use an ASTA approved one (conforming to BS 1362 of the same rating).

If in doubt, consult a qualified electrician who will be pleased to do this for you.

If you need to remove the plug - DISCONNECT IT FROM THE MAINS and then cut it off the mains lead and immediately dispose of it safely. Never attempt to reuse the plug or insert it into a socket outlet as there is a danger of an electric shock.

**UP Global Sourcing UK Ltd.,
UK. Manchester OL9 0DD.
Germany. 51149 Köln.**

If this product does not reach you in an acceptable condition please contact our Customer Services Department at **www.beldray.com**

Please have your delivery note to hand as details from it will be required.

If you wish to return this product please return it to the retailer from where it was purchased with your receipt (subject to their terms and conditions).

Guarantee

All products purchased as new carry a manufacturer's guarantee; the time period of the guarantee will vary dependent upon the product. Where reasonable proof of purchase can be provided, Beldray will provide a standard 12 month guarantee with the retailer from the date of purchase. This is only applicable when products have been used as instructed for their intended, domestic use. Any misuse or dismantling of products will invalidate any guarantee.

Under the guarantee, we undertake to repair or replace free of any charge any parts found to be defective. In the event that we cannot provide an exact replacement, a similar product will be offered or the cost refunded. Any damages from daily wear and tear are not covered by this guarantee, nor are consumables such as plugs, fuses etc.

Please note that the above terms and conditions may be updated from time to time and we therefore recommend that you check these each time you revisit the website.

Nothing in this guarantee or in the instructions relating to this product excludes, restricts or otherwise affects your statutory rights.

The crossed out wheelie bin symbol on this item indicates that this appliance needs to be disposed of in an environmentally friendly way when it becomes of no further use or has worn out. Contact your local authority for details of where to take the item for recycling.





*To be eligible for the extended guarantee,
go to www.beldray.com and register your product
within 30 days of purchase.

Find us on 

www.facebook.com/Beldray



Manufactured by:
UP Global Sourcing UK Ltd.,
UK. Manchester OL9 0DD.
Germany. 51149 Köln.

www.beldray.com

©Beldray Trademark. All rights reserved.


CD110419/MD210621/V4



ULTIMATE PRODUCTS
HOME OF BRANDS

Manchester
OL9 0DD
United Kingdom
www.upgs.com

Artworker:	Scarlett Chester-Roberts
Date:	21/06/2021
Project Name:	HCH191304 UPG EH0197SSTK
Type of Artwork:	Instruction Manual
Size:	A5 12 PP
Software Used:	IndDesign CC21
Typefaces:	Avenir Next, ITC Lubalin Graph



Artwork Version 4

Artwork Scale 1:1

©2021 UP Global Sourcing. All designs, images and artwork are the copyright of UP Global Sourcing. No copying, alterations or amendments to the artwork, design can be undertaken without prior written permission of UP Global Sourcing. Any costs incurred as a result of unauthorised amendments will be recovered from the supplier responsible.

DO NOT PRINT THIS PAGE
ARTWORK REFERENCE ONLY