



TECHNICAL INFORMATION



V4 Substantial
Variation



Ready Ship



DCOF: ≥ 0.55



Frost Resistant



Water Absorption:
≤ 0.5%



Made in USA



COLORS



Matterhorn
VTC YOMH



Lyll
VTC YOLY



Conness
VTC YOEN

Performance Characteristics

Breaking Strength	2000 lbf
Chemical Resistance	Resistant
DCOF	≥ 0.55
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	N/A
Water Absorption	≤ 0.5%
Certifications	N/A
Country of Origin	USA
Shade Variation Code	V4

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
12" x 12" Rectified	12" x 12"	20mm	Bush-hammered/R11
12" x 24" Rectified	12" x 24"	9mm	Matte/Natural
24" x 24" Rectified	24" x 24"	20mm	Bush-hammered/R11
3" x 12" Rectified	3" x 12"	9mm	Matte/Natural
1" x 3" Mosaic Rectified	12" x 12"	9mm	Matte/Natural
2" x 2" Mosaic Rectified	12" x 12"	9mm	Matte/Natural
3" x 24" Bullnose	3" x 24"		Matte/Natural

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

** These recommendations are not defined by ANSI Standards



Please see virginiatile.com for details