



NEW! HML2

CAST ALUMINUM HOUSING

Allows operation up to 131°F (55°C)

COMPACT DESIGN

Impressive light output in a compact 12.6"x23" design

WATTAGE SELECTABLE

Fixture offers selectable wattage 320W/270W/220W

INTEGRATED SENSOR SOCKET

Integrated sensor socket allows the use of low-voltage lighting controls

LENS OPTIONS

Diffused lens reduces glare. Optional aisle and wide distribution lenses available



NICOR'S NEW ULTRA-EFFICIENT, HIGH PERFORMANCE HIGH BAY

NICOR introduces the newest high bay product line: the patent pending, ultra-efficient, high performance HML2 high bay. With only a 12.6"x23" footprint its compact design offers an impressive light output with simple, single-person installation. The DLC 5.1 Premium certified fixture offers selectable wattage (320W/270W/220W), sensor, and aisle distribution options. It's durable single-piece cast aluminum design is perfect for rugged applications like warehouses, gymnasiums, and other industrial or commercial spaces.

Ordering Information

Example: HML2320WSU50A

Series	Version	Wattage	Input Voltage	CCT	Distribution	Sensor Socket	Emergency	Wiring Options
HML	2	320WS (320/270/220W)	U (120-277V)	35 (3500K)	A (General 90°x90°)	S (With Socket)	Blank (No)	Blank (No)
			H (277-480V)	40 (4000K)	B (Wide 105°x105°)		E40 (40W)	C3 (Cord-3-wire, 6ft)
				50 (4000K)	C (Aisle 45°x100°)			C4 (Cord-4-wire, 6ft)
				57 (5700K)				F (Flex Conduit - 6ft)

*See spec sheet for detailed ordering chart.



Warehouse Locations:

Albuquerque, NM Detroit, MI
Atlanta, GA Folcroft, PA
Buford, GA Roseville, CA

Contact NICOR Lighting:

T: 800.821.6283
www.nicorlighting.com
2200 Midtown Pl. NE
Albuquerque, NM 87107 USA