

TECHNICAL INFORMATION



V2 Slight Variation



Stock Ready Ship



Recommend offset pattern ≤33%



DCOF: > 0.42



Frost Resistant



Water Absorption: < 0.5%



Made in Turkey



Greenguard



COLORS



Light Gray | VTC NILI



Medium Gray | VTC NIME



Dark Gray | VTC NIDA



Black | VTC NIBL

PERFORMANCE CHARACTERISTICS

Breaking Strength	>1600
Chemical Resistance	N/A
DCOF	>0.42
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	8
Water Absorption	N/A
Certifications	Greenguard
Country of Origin	Turkey
Shade Variation Code	V2

TILES, MOSAIC AND TRIM*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 47" Rectified	23.62" x 47.24"	10.30mm	Matte/Natural
24" x 24" Rectified	23.62" x 23.62"	9.30mm	Matte/Natural
12" x 24" Rectified	11.81" x 23.62"	8.40mm	Matte/Natural
6" x 6" Hex Mosaics	9.96" x 11.50"	8.40mm	Matte/Natural
2" x 2" Hex Mosaics	11.73" x 11.85"	8.40mm	Matte/Natural
2" x 2" Mosaic	11.77" x 11.77"	8.40mm	Matte/Natural
3" x 24" Bullnose	2.76" x 23.62"	8.40mm	Matte/Natural

* Not all sizes are available in all colors and finishes.

APPLICATION**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Please see virginiatile.com for details.

