

WAC LIGHTING

7"/11" Square

Ceiling and Wall Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
<input type="radio"/> FM-07SQ 7"	<input type="radio"/> 930 3000K - 90	15W	1100	<input type="radio"/> BN Brushed Nickel
<input type="radio"/> FM-11SQ 11"	<input type="radio"/> 935 3500K - 90	15W	1100	<input type="radio"/> BZ Bronze
	<input type="radio"/> 930 3000K - 90	20W	1650	<input type="radio"/> WT White
	<input type="radio"/> 935 3500K - 90	20W	1650	

Example: **FM-07SQ-930-BN**

DESCRIPTION

Ultra-slim flush mount that uses edge-lit technology and a translucent diffuser for uniform illumination without shadows or hotspots.

FEATURES


- Multiple LED array for uniform illumination
- Driver installed within the Junction Box, driver dimension: 2.25" dia x 1" deep
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with translucent diffuser
Power:	15W, 20W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: Bronze, White, Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Energy Star 2.0, ADA, Title 24 JA8 Compliant



FINISHES:



LINE DRAWING:

