

Vellum



Colors



White
VTL VLWH



Beige
VTL VLBE



Gray
VTL VLGR



Blue
VTL VLBL

Sizes



6" x 6" x 9.5mm



3" x 8" x 9.5mm



2" x 6" x 9.5mm

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
6" x 6"	5.88" x 5.88"	9.50mm	Gloss
3" x 8"	2.94" x 7.88"	9.50mm	Gloss
2" x 6"	1.94" x 5.88"	9.50mm	Gloss
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
6" x 6" Bloom Decorative	5.88" x 5.88"	Gloss
3" x 8" Binding Decorative	2.94" x 7.88"	Gloss
2" x 6" Bud Decorative	1.94" x 5.88"	Gloss
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

	GLOSS
Breaking Strength (ASTM C648 or ISO 10545-4)	>275 lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	N/A
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	N/A
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	<0.5%
Certifications	N/A
Country of Origin	N/A
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	
Interior	Commercial	•	
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		

** These recommendations are not defined by ANSI Standards

Material

Glazed Porcelain



Ready Ship



V2 Slight Variation



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

