



Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------



General

Provided equipment	Installation guide Rack Mounting support rails USB cable
--------------------	--

Physical

Cable length	8 ft (2.44 m)
Number of rack unit	2U
Color	Black
Maximum Depth	18.78 in (47.7 cm)
Maximum Height	3.39 in (8.6 cm)
Net Weight	58.42 lb(US) (26.5 kg)
Maximum Width	17.01 in (43.2 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Other Input Voltages	110 V 125 V
Nominal Input Voltage	120 V

Output

Kw Rating	1000 W
Max Configurable Power (Watts)	1000 W
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Other Output Voltages	110 V 125 V
Topology	Line Interactive
Waveform Type	Sine wave
Nb of power socket outlets	6 NEMA 5-15R
Output voltage	120 V

Conformance

Product certifications	CULus ENERGY STAR V2.0 (USA)
Standards	CSA C22.2 No. 107.1 FCC Part 15 class A ICES-003 UL 1778
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Online Thermal Dissipation	225 Btu/h

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Liquid Electrolyte Value	0

Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304322801
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	9.25 in (23.5 cm)
Package 1 width	23.23 in (59 cm)
Package 1 Length	24.02 in (61 cm)
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---