

FLOOR TILE



Elegant



Sophisticated



Distinguished

2 x 2 SQUARE MOSAIC
12 x 12 SHEET



Elegant



Sophisticated



Distinguished

MIXED DECOS



Mixed Mosaic 12 x 12 Sheet








Listelli 2 x 12

USAGE

Floors	Walls	Countertops
F	W	C


SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	18 x 36 Floor Tile	(17-11/16" x 35-7/16") (45.00 cm x 90.00 cm)	3/8"	13.44	3
	12 x 24 Floor Tile	(11-13/16" x 23-5/8") (30.00 cm x 60.00 cm)	5/16"	17.37	9
	2 x 2 Square Mosaic (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm)	5/16"	10.00	10
	Mixed Mosaic (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm)	5/16"	---	10
	Listelli 2 x 12	(2" x 12") (5.08 cm x 30.48 cm)	3/8"	---	6

TRIM

Description	Size	Shape
Floor Bullnose	4 x 24	

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) Mosaic: 1/8"	 High Variation

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

*2 x 2 Mosaic tile only.

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazzitile.com.

	Floor Tile		Deco			Trim			
	18 x 36	12 x 24	2 x 2 Square Mosaic 12 x 12 Sheet	Mixed Mosaic 12 x 12 Sheet	2 x 12 Listelli	4 x 24 Floor Bullnose	6 x 12 Cove Base	1 x 6 Cove Base Outcorner	1 x 6 Cove Base Incorner
Distinguished	ULBP	ULBL	ULEW			ULBV	ULC6	ULC3	ULBY
Elegant	ULBM	ULBJ	ULEU			ULBT	ULC4	ULBZ	ULBW
Sophisticated	ULBN	ULBK	ULEV			ULBU	ULC5	ULC2	ULBX
Mixed				ULE8	ULEE				