Locking Devices, Twist-Lock®, Industrial, Male Plug, 30A 250V, 2-Pole 3-Wire Grounding, L6-30P, Screw Terminal, Black and White

By Hubbell Wiring Device-Kellems Catalog # HBL2621

Locking Devices, Twist-Lock®, Industrial, Male Plug, 30A 250V, 2-Pole 3-Wire Grounding, L6-30P, Screw Terminal, Black and White.



General

Application Catalog Number Color Cord Range EU RoHS Indicator **Environmental Conditions**

Horsepower - Maximum Item Type Material Material - Mounting Hardware Number Of Poles Operating Temperature

Performance

HBL2621 0.360"-0.930" (9-24) Yes Indoor Dry Unless Protected By Additional Means 2

30A Grounding Insulgrip® Plug Nylon Cord Mounted 2-Pole Maximum continuous 75°C and minimum -40°C without Impact Electrical - Current Interrupting

> current Electrical - Dielectric Voltage -Withstands 2,000V minimum

- Certified for current interrupting at full rated

Environmental - Flammability -HB or better per UL94/CSA 22.2 No.0.17

Environmental - Moisture Resistance - IP20 Suitability

Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)

Mechanical - Terminal Accommodation - #16 AWG -#8 AWG stranded copper wire only.

Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Plugs Plugs

783585038834

Dimensions

Туре

UPC

Dimensions Display Size Height Length Weight Width

2.26 in x 2.26 in x 2.75 in Standard Sized 2.75 in 2.26 in 0.25 lb 2.26 in

Electrical Ratings

30 A Amperage Rating Connectivity Pressure Terminal Screws Current / Amperage Rating 30 A **Current Rating** 30 A Dielectric Strength Withstands 2,000V minimum Phase Single Phase 250 VAC Voltage Rating Voltage Rating Description 250 VAC

Conductor Related

Cable Range	0.360 - 0.930 in
Cord Type	All Listed Portables
Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Certifications And Compliance

Certified to CSA C22.2 No.42
Fed.Spec. W-C-596
Listed to UL 498
L6-30P
СМ

Logistics

Carton Quantity	30
Pallet Quantity	2550

Product Assets

Catalogs - WDK Catalog Full 2024 Warranty - Industrial & Commercial Products



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved WDK_MX-HBL2621-SPEC-EN | REV 6/2024