

**206103, 206105**  
**INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions as you may need them a later date.

**CAUTION**

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

**ASSEMBLY AND INSTALLATION**

1. Attach the mounting bar (7) with box screws (8) to the outlet box.
2. Thread the central tube (2) onto the socket assembly (1) to secure.
3. Thread the central ball (4) onto the central tube (2) to secure.
4. Thread the loop (5) onto the central ball (4) to secure.
5. Attach the quick link of the chain (13) onto the shade (14) and central ball (4). Fully close the quick link.
6. Attach one end of the quick link (6) with chain to the loop (5). Fully close the quick link (6).
7. Weave the fixture wires through the following components: chain links (skipping every other link), the canopy loop ring (12), canopy loop (11), and finally through the canopy (10). Ensure there is enough wire length to reach the junction box.
8. Attach another end of the quick link (6) onto the canopy loop (11). Fully close the quick link (6).
9. Pull out the outlet wire and ground wire from the outlet box.
10. Make wire connections with wire nut (9).
  - Connect the ribbed wire w/o marking (Neutral wire) or white wire from the light to the white wire from power source.
  - Connect the wire with the markings and smooth surface (Live wire) or black wire from the light to the black wire from power source.
  - Wrap the grounding wire (green wire or bare copper wire) from the light around the green screw on the mounting bar (7), then connect it to the grounding conductor from power source.
11. Screw the canopy loop (11) onto the mounting bar (7). Attach the fixture canopy (10) to the outlet box by tightening the canopy loop ring (12) onto the canopy loop (11).
12. Install 60W Max. A19 bulbs (bulbs not included).  
(Don't exceed the maximum capacity recommended on the sockets).

