

Features

- High-quality solid-brass construction for durability and reliability
- Required shower arm sold separately
- 2.5 gpm (9.5 lpm) maximum flow rate
- Single-function spray
- Includes escutcheon
- Air-induction technology maximizes the air/water mix for a powerful, even flow

Required Products/Accessories

P21520-00 Rain Showerhead Arm

or

P21521-00 Rain Showerhead Arm

or

P21522-00 12" ceiling-mount rain showerhead arm

or

P21523-00 Wall-Mount Rain Showerhead Arm



Codes/Standards








ASME A112.18.1/CSA B125.1

KALLISTA® Five-Year Limited Warranty

See website for detailed warranty
information.


Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BL	Matte Black
	ULB	Unlacquered Brass
	AF	French Gold
	BAF	Brushed French Gold
	BN	Brushed Nickel
	BV	Brushed Bronze
	SN	Polished Nickel
	2MB	Brushed Moderne Brass

KALLISTA

Foundations by KALLISTA
Air-induction oversized contemporary rain
showerhead
P26139-00



Technical Information

All product dimensions are nominal.

Drain included: No

Shower/Rainhead rated max flow: 2.5 gal/min (9.5 l/min)